

## ABS Cement (Black)-Medium Bodied



### DESCRIPTION

**Black Swan ABS Cement - Medium** is a black, medium bodied, medium to fast set, high strength ABS solvent cement used to join ABS pipe and fittings. For all classes and schedules through 6" diameter. Do not use primer of any kind on ABS pipe and fittings when making joints. ABS Cement is most effective when used in temperature ranges from 40°F to 100°F.

---

### SHELF LIFE

ABS Cement has a shelf life of two years from date on bottom of can.

---

### STANDARDS AND APPROVALS

ABS Cement meets ASTM D-2235 and is listed by NSF International for sewer pipe and drain, waste & vent systems.

---

### PACKAGING

ABS Cement is available in 1/4 pint, 1/2 pint, pint, quart, gallon and 5 gallon containers. Larger sizes available upon request. On sizes smaller than one gallon there is a dauber in each container to facilitate application of cement.

### UPC NUMBER AND CARTON INFORMATION

<b>STOCK NO.</b>	<b>SIZE</b>	<b>UPC NUMBER</b>	<b>CARTON CUBIC FEET</b>
07260	1/4 pt.	0 54647 07260 9	.222
07265	1/2 pt.	0 54647 07265 4	.385
07270	pt.	0 54647 07270 8	.376
07275	qt.	0 54647 07275 3	.711
07280	gal.	0 54647 07280 7	1.000
07285	5 gal.	0 54647 07285 2	1.375

