



Project/Job Name:

Location:

Fixture Type:

Notes:

65-900 - Bullet Outdoor SMART Security Camera; Starfish enabled; White Finish

• Has Camera

• IOT Enabled











ELECTRICAL

Watts:20WVolts:120V-277VLumens:1900LLamp Base :IntegratedLamp Shape :Integrated LEDCRI:80CCT (Kelvins):3000KColor Description:Warm WhiteBeam Spread :50Hours Rated:50000Dimmable:Yes-DimmableDimmable Down To %:100 to 20 percentDimmableText:Only with Starfish AppDimming Type :Smart-Starfish App onlyIncandescent Equivalent :100WHID Equivalent :72WOperating Temperature :-20C (-4F) to +60C (+140F)Lamp Included :IntegratedReplaceable Light Source :NoConnection:HardwireSurge Protection :Built-in surge protection - 2KVVoltage Type:Range VoltageWarranty:5 Year Limited - Fixtures	Technology:	LED
Lumens: 1900L Lamp Base: Integrated Lamp Shape: Integrated LED CRI: 80 CCT (Kelvins): 3000K Color Description: Warm White Beam Spread: 50 Hours Rated: 50000 Dimmable: Yes-Dimmable Dimmable Down To %: 100 to 20 percent DimmableText: Only with Starfish App Dimming Type: Smart-Starfish App only Incandescent Equivalent: 100W HID Equivalent: 72W Operating Temperature: -20C (-4F) to +60C (+140F) Lamp Included: Integrated Replaceable Light Source: No Connection: Hardwire Surge Protection: Built-in surge protection - 2KV Voltage Type: Range Voltage	Watts:	20W
Lamp Base :IntegratedLamp Shape :Integrated LEDCRI:80CCT (Kelvins):3000KColor Description:Warm WhiteBeam Spread :50Hours Rated:50000Dimmable:Yes-DimmableDimmable Down To %:100 to 20 percentDimmableText:Only with Starfish AppDimming Type :Smart-Starfish App onlyIncandescent Equivalent :100WHID Equivalent :72WOperating Temperature :-20C (-4F) to +60C (+140F)Lamp Included :IntegratedReplaceable Light Source :NoConnection:HardwireSurge Protection :Built-in surge protection - 2KVVoltage Type:Range Voltage	Volts:	120V-277V
Lamp Shape: CRI: CRI: So CCT (Kelvins): Color Description: Beam Spread: Hours Rated: Dimmable: Dimmable: Dimmable Down To %: Dimmable Text: Dimming Type: Smart-Starfish App only Incandescent Equivalent: HID Equivalent: Coperating Temperature: Lamp Included: Replaceable Light Source: Connection: Built-in surge protection - 2KV Voltage Type: Range Voltage	Lumens:	1900L
CRI: CCT (Kelvins): Soook Color Description: Warm White Beam Spread: Hours Rated: Dimmable: Dimmable: Dimmable Down To %: Dimmable Text: Dimmable Text: Dimming Type: Smart-Starfish App only Incandescent Equivalent: HID Equivalent: Toow HID Equivalent: Toow HID Equivalent: Toow Connection: Hardwire Surge Protection: Built-in surge protection - 2KV Voltage Type: Smart-Starfish App Built-in surge protection - 2KV Range Voltage	Lamp Base :	Integrated
CCT (Kelvins): Color Description: Warm White Beam Spread: Hours Rated: Dimmable: Dimmable Down To %: Dimmable Down To %: Dimmable Text: Only with Starfish App Dimming Type: Smart-Starfish App only Incandescent Equivalent: 100W HID Equivalent: Operating Temperature: Lamp Included: Replaceable Light Source: No Connection: Built-in surge protection - 2KV Voltage Type: Smart-Starfish App only Integrated Replaceable Light Source: Range Voltage	Lamp Shape :	Integrated LED
Color Description: Warm White Beam Spread: 50 Hours Rated: 50000 Dimmable: Yes-Dimmable Dimmable Down To %: 100 to 20 percent DimmableText: Only with Starfish App Dimming Type: Smart-Starfish App only Incandescent Equivalent: 100W HID Equivalent: 72W Operating Temperature: -20C (-4F) to +60C (+140F) Lamp Included: Integrated Replaceable Light Source: No Connection: Hardwire Surge Protection: Built-in surge protection - 2KV Voltage Type: Range Voltage	CRI:	80
Beam Spread: 50 Hours Rated: 50000 Dimmable: Yes-Dimmable Dimmable Down To %: 100 to 20 percent DimmableText: Only with Starfish App Dimming Type: Smart-Starfish App only Incandescent Equivalent: 100W HID Equivalent: 72W Operating Temperature: -20C (-4F) to +60C (+140F) Lamp Included: Integrated Replaceable Light Source: No Connection: Hardwire Surge Protection: Built-in surge protection - 2KV Voltage Type: Range Voltage	CCT (Kelvins):	3000K
Hours Rated: 50000 Dimmable: Yes-Dimmable Dimmable Down To %: 100 to 20 percent DimmableText: Only with Starfish App Dimming Type: Smart-Starfish App only Incandescent Equivalent: 100W HID Equivalent: 72W Operating Temperature: -20C (-4F) to +60C (+140F) Lamp Included: Integrated Replaceable Light Source: No Connection: Hardwire Surge Protection: Built-in surge protection - 2KV Voltage Type: Range Voltage	Color Description:	Warm White
Dimmable: Dimmable Down To %: Dimmable Down To %: Dimmable Text: Dimmable Text: Dimming Type: Smart-Starfish App only Incandescent Equivalent: 100W HID Equivalent: Operating Temperature: -20C (-4F) to +60C (+140F) Lamp Included: Replaceable Light Source: Connection: Surge Protection: Built-in surge protection - 2KV Voltage Type: Range Voltage	Beam Spread :	50
Dimmable Down To %: Dimmable Text: Only with Starfish App Dimming Type: Smart-Starfish App only Incandescent Equivalent: 100W HID Equivalent: Operating Temperature: -20C (-4F) to +60C (+140F) Lamp Included: Replaceable Light Source: No Connection: Surge Protection: Built-in surge protection - 2KV Voltage Type: 100 to 20 percent 100 to 20 per	Hours Rated:	50000
DimmableText: Only with Starfish App Dimming Type: Smart-Starfish App only Incandescent Equivalent: HID Equivalent: Operating Temperature: -20C (-4F) to +60C (+140F) Lamp Included: Integrated Replaceable Light Source: No Connection: Surge Protection: Built-in surge protection - 2KV Voltage Type: Range Voltage	Dimmable:	Yes-Dimmable
Dimming Type: Incandescent Equivalent: HID Equivalent: Operating Temperature: Lamp Included: Replaceable Light Source: Connection: Surge Protection: Dimming Type: Smart-Starfish App only 100W 10	Dimmable Down To %:	100 to 20 percent
Incandescent Equivalent: HID Equivalent: Operating Temperature: Lamp Included: Replaceable Light Source: Connection: Surge Protection: Voltage Type: Incomposition 100 W 72W 72W 72W 100 W 100 W	DimmableText:	Only with Starfish App
HID Equivalent: 72W Operating Temperature: -20C (-4F) to +60C (+140F) Lamp Included: Integrated Replaceable Light Source: No Connection: Hardwire Surge Protection: Built-in surge protection - 2KV Voltage Type: Range Voltage	Dimming Type :	Smart-Starfish App only
Operating Temperature: -20C (-4F) to +60C (+140F) Lamp Included: Replaceable Light Source: Connection: Surge Protection: Voltage Type: Range Voltage	Incandescent Equivalent :	100W
Lamp Included: Integrated Replaceable Light Source: No Connection: Hardwire Surge Protection: Built-in surge protection - 2KV Voltage Type: Range Voltage	HID Equivalent :	72W
Replaceable Light Source :NoConnection:HardwireSurge Protection :Built-in surge protection - 2KVVoltage Type:Range Voltage	Operating Temperature :	-20C (-4F) to +60C (+140F)
Connection: Hardwire Surge Protection : Built-in surge protection - 2KV Voltage Type: Range Voltage	Lamp Included :	Integrated
Surge Protection : Built-in surge protection - 2KV Voltage Type: Range Voltage	Replaceable Light Source :	No
Voltage Type: Range Voltage	Connection:	Hardwire
	Surge Protection :	Built-in surge protection - 2KV
Warranty: 5 Year Limited - Fixtures	Voltage Type:	Range Voltage
	Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923659683
Each Quantity:	1
Each Dimensions:	8.58 x 8.07 x 9.69
Case UPC:	10045923659680
Case Quantity:	5
Case Dimensions:	41.34 x 9.17 x 10.32

PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Glass
Finish Family:	White
Dimensions:	W:8.27" H:8.46" E:9.44"
Weight (Lbs.):	2.78
Material:	Die-cast Aluminum
Sensor:	Has PIR Sensor
·	

IOT

IOT Enabled:	Yes
Operational Humidity:	20% to 85% non-condensing
Communication Protocol:	802.11b/g/n; WPA/WPA2; WPA-
	PSK/WPA2-PSK
Software Supported:	AWS Cloud Security Servers
Storage Capactiy:	Digital Wide Dynamic

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outoor:	Outdoor
Energy Star Qualified:	No
DLC Approved:	No
CA Prop 65:	Lead
BAA Compliant:	No
ADA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP65
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

INFO

Installation Note:	May be wired to recessed or external junction boxes.