



Clutch Cable Bracket



Parts Needed:

- Clutch Cable Bracket

Weekend Project Category:

- Appearance

Fits The Following Motorcycles:

- Triumph Modern Classics
- Triumph America & Speedmaster

Difficulty:



Tools Required:

- 4 mm Allen wrench

Time it Takes to Install:

- 10 minutes

WARNING: Laws concerning this product vary from state/province to state/province. Your state/province may prohibit its use on public roads or restrict its use to novelty, show use, off-road areas, or race facility areas only. In some states/provinces off-road uses are also prohibited. The manufacturer and retailer assume no responsibility for any use or application of this product in violation of any applicable law. Before installing this product, please check your state/province and local/municipal laws and regulations.

WARNING: It is recommended that this kit be installed by a certified Triumph technician, following the Triumph service manual to aid in proper fitting. Verify all torque specs in Triumph service manual.

Related Weekend Project Upgrades



Clutch Arm Lifter Finisher



Oil Pressure Gauge



Passenger Peg Block Off



Rectifier Relocation Bracket

Clutch Cable Bracket



Step 1: Disengage clutch cable from lifter arm

Loosen clutch cable by using the lock nut beside the clutch cable bracket. Pull cable out of clutch lifter arm.



Step 2: Install gaiter and reattach clutch cable

Use 4mm wrench to remove stock clutch cable bracket. Use 4mm wrench to install BC Clutch Cable Bracket.



Step 3: Install BC Clutch Cable Bracket

Run clutch cable through BC Clutch Cable Bracket. Reattach clutch cable to clutch arm. Tighten clutch cable using locknut to proper tension.



Installation complete!