



An APPLIED MSS™ company

## Tru-Galv® QWIK-DRY

### 065-017-044

#### PRODUCT DESCRIPTION

Hub Industrial Supply QWIK-DRY is a sacrificial coating that inhibits rust and corrosion to ferrous metals. An excellent fast drying touchup for repair of galvanized substrates. This coating has the bright finish of a hot-dip galvanized coating.

#### USES

- Refineries
- Welds
- Fences
- Gutters
- Bridges
- Damaged galvanized surfaces
- Highway maintenance
- Nuclear facilities
- Transmission towers
- Structural steel
- Wrought iron
- Power plants
- Farm equipment
- Automotive
- Marine

#### APPLICATION

Must be applied directly to dry, clean metal or galvanized surfaces and not over any other paint or coating. Proper surface preparation contributes to maximum service life of coatings. All contaminants (mill scale, rust, rust scale, chemicals, grease, oil, wax, weld spatter, old paint or other foreign matter must be removed down to bare metal.

Product should be sprayed in a well ventilated area. Sprays best between 50°F (10°C) and 90°F (32°C). Shake well before using. Spray at a distance of 8" to 10" from surface.

#### DIRECTIONS FOR USE

##### Preparation

- Remove all rust, scale, paint, grease or foreign matter. A good clean surface is necessary.
- Apply directly to DRY metal or galvanized surface and not over any other paint or coating.
- Product should be sprayed in a well-ventilated area.
- Use between 50°F (10°C) and 90°F (32°C).

##### For Best Results:

- Turn can upside down.
- Hit sides lightly while rotating can 1/4 turns until steel mixing ball breaks loose.
- Shake can at least one minute after rattle is heard and repeat after each minute of use.
- Press spray button firmly with the can 8" to 12" from surface being coated. Move can with short dusting strokes, releasing button at the end of each stroke. Apply several thin coats.
- To prevent clogging, clear the valve by holding can upside down and spray until only clear gas comes out.

#### PROPERTIES

**RESIN TYPE:** Acrylic

**APPEARANCE:** Silver Gray

**GLOSS:** Flat, <15 on 60° gloss meter

**% SOLIDS:** 9%

**DRY FILM WEIGHT:** 65.5% zinc

**FLAMMABILITY:** Extremely flammable

**HAPS CONTENT:** 15%

**SPECIFIC GRAVITY:** 0.87

**HAZARD CODE:** 2,3,1

**VOC:** 52.50%

**MIR:** 0.73

**OTC & CALIFORNIA COMPLIANT:** Yes

**STORAGE TEMP:** 40-100° F

**FLASH POINT:** < -4° F

**RECOMMENDED FILM THICKNESS:**  
1 - 3.0 mils

**COVERAGE PER AEROSOL (THEORETICAL):** 10-15 sq ft.

**SHELF LIFE:** 24 months

**DRYING TIME @ 70°F @ 50%R.H.**

**TO TOUCH:** 5 minutes

**TO HANDLE:** 20 minutes

**RECOAT:** 20 minutes

**CLEAN UP:** Paint or laquer thinner

**SIZE:** 16 oz can; 13 oz (369 grams) by weight

**DURABILITY:** Very Good

**ABRASION RESISTANCE:** Good

## RESISTANCE GUIDE

**ASTM A780-01 (Standard Practice for Repair of Damaged and Uncoated Areas of Hot-Dip Galvanized Coatings):** Yes

- Excellent touch-up of galvanized surfaces
- Bright finish of hot-dipped surfaces
- Good Corrosion resistance

**DRY HEAT RESISTANCE:** 250°F

**HUB**  
INDUSTRIAL SUPPLY  
An APPLIED MSS™ company  
P.O. Box 3609  
Lake City, FL 32056  
(800) 743-9401  
[www.hubindustrialsupply.com](http://www.hubindustrialsupply.com)