

Dykem® Remover & Prep (Aerosol)

ITW Pro Brands. -GA

Part Number: 82038

Version No: 2.4

Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: 10/12/2023

Revision Date: 03/10/2025

Print Date: 08/10/2025

S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Dykem® Remover & Prep (Aerosol)
Proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Other means of identification	Not available

Recommended use of the chemical and restrictions on use

Relevant identified uses	For Industrial Use Only Use according to manufacturer's directions.
--------------------------	--

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ITW Pro Brands. -GA
Address	4647 Hugh Howell Rd. Tucker, GA United States
Telephone	770-243-8800
Fax	Not Available
Website	www.itwprobrands.com
Email	lpssds@itwprobrands.com

Emergency phone number

Association / Organisation	Dykem/Dymon/Scrubs = Call InfoTrac For _LPS & Other Brands = Call Chemtrec
Emergency telephone number(s)	1-800-535-5053 (InfoTrac Inside US) 1-800-424-9300 (Chemtrec Inside US)
Other emergency telephone number(s)	1-352-323-3500 (Infotrac Outside US) +001 703-527-3887 (Chemtrec Outside US)

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

Classification	Aerosols, Hazard Category 1, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3
----------------	--

Label elements

Hazard pictogram(s)	 
Signal word	Danger

Hazard statement(s)

H222+H229	Extremely flammable aerosol. Pressurized container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing gas.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
67-64-1	45-70	ACETONE* (R)
64-17-5	10-30	ETHANOL(R)
68476-86-8.	10-30	LPG (liquefied petroleum gas) sweetened
109-60-4	1-5	n-propyl acetate
67-63-0	1-3	ISOPROPANOL*(R)

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If aerosols come in contact with the eyes: ▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If solids or aerosol mists are deposited upon the skin: ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in the event of irritation.
Inhalation	If aerosols, fumes or combustion products are inhaled: ▶ Remove to fresh air. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	Not considered a normal route of entry. ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.

- BCF (where regulations permit).
 - Carbon dioxide.
 - Water spray or fog - Large fires only.
- SMALL FIRE:**
- Water spray, dry chemical or CO2
- LARGE FIRE:**
- Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility	‣ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Special protective equipment and precautions for fire-fighters

Fire Fighting	GENERAL ‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ May be violently or explosively reactive. ‣ Wear breathing apparatus plus protective gloves. ‣ Consider evacuation ‣ Fight fire from a safe distance, with adequate cover. ‣ If safe, switch off electrical equipment until vapour fire hazard removed. ‣ Use water delivered as a fine spray to control fire and cool adjacent area. ‣ DO NOT approach cylinders suspected to be hot. ‣ Cool fire-exposed cylinders with water spray from a protected location. ‣ If safe to do so, remove containers from path of fire. FIRE FIGHTING PROCEDURES: ‣ The only safe way to extinguish a flammable gas fire is to stop the flow of gas. ‣ If the flow cannot be stopped, allow the entire contents of the cylinder to burn while cooling the cylinder and surroundings with water from a suitable distance. ‣ Extinguishing the fire without stopping the gas flow may permit the formation of ignitable or explosive mixtures with air. These mixtures may propagate to a source of ignition. SPECIAL HAZARDS ‣ Excessive pressures may develop in a gas cylinder exposed in a fire; this may result in explosion. ‣ Cylinders with pressure relief devices may release their contents as a result of fire and the released gas may constitute a further source of hazard for the fire-fighter. ‣ Cylinders without pressure-relief valves have no provision for controlled release and are therefore more likely to explode if exposed to fire. FIRE FIGHTING REQUIREMENTS: The need for proximity, entry and flash-over protection and special protective clothing should be determined for each incident, by a competent fire-fighting safety professional. Prevent by any means spillage from entering drains or water-courses.
Fire/Explosion Hazard	‣ Liquid and vapour are flammable. ‣ Moderate fire hazard when exposed to heat or flame. ‣ Vapour forms an explosive mixture with air. ‣ Moderate explosion hazard when exposed to heat or flame. ‣ Vapour may travel a considerable distance to source of ignition. ‣ Heating may cause expansion or decomposition leading to violent rupture of containers. ‣ Aerosol cans may explode on exposure to naked flame. ‣ Rupturing containers may rocket and scatter burning materials. ‣ Hazards may not be restricted to pressure effects. ‣ May emit acrid, poisonous or corrosive fumes. ‣ On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	‣ Clean up all spills immediately. ‣ Avoid breathing vapours and contact with skin and eyes. ‣ Wear protective clothing, impervious gloves and safety glasses. ‣ Shut off all possible sources of ignition and increase ventilation. ‣ Wipe up. ‣ If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. ‣ Undamaged cans should be gathered and stowed safely.
Major Spills	‣ DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve. ‣ Clear area of personnel and move upwind. ‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ May be violently or explosively reactive. ‣ Wear breathing apparatus plus protective gloves. ‣ Prevent, by any means available, spillage from entering drains or water courses ‣ No smoking, naked lights or ignition sources. ‣ Increase ventilation.

Dykem® Remover & Prep (Aerosol)

- ▶ Stop leak if safe to do so.
- ▶ Water spray or fog may be used to disperse / absorb vapour.
- ▶ Absorb or cover spill with sand, earth, inert materials or vermiculite.
- ▶ If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.
- ▶ Undamaged cans should be gathered and stowed safely.
- ▶ Collect residues and seal in labelled drums for disposal.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ Avoid smoking, naked lights or ignition sources. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ DO NOT incinerate or puncture aerosol cans. ▶ DO NOT spray directly on humans, exposed food or food utensils. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. NFPA 30B Storage Level: 3
Other information	▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can ▶ Store in original containers in approved flammable liquid storage area. ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped. ▶ No smoking, naked lights, heat or ignition sources. ▶ Keep containers securely sealed. Contents under pressure. ▶ Store away from incompatible materials. ▶ Store in a cool, dry, well ventilated area. ▶ Avoid storage at temperatures higher than 40 deg C. ▶ Store in an upright position. ▶ Protect containers against physical damage. ▶ Check regularly for spills and leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Do not cut, drill, grind, weld or perform similar operations on or near containers. Containers, even those that have been emptied, can contain explosive vapours.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Aerosol dispenser. ▶ Check that containers are clearly labelled.
Storage incompatibility	Avoid reaction with oxidising agents. ▶ Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances



X — Must not be stored together
0 — May be stored together with specific preventions
+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	ACETONE* (R)	Acetone	1000 ppm / 2400 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ACETONE* (R)	Acetone	250 ppm / 590 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	ISOPROPANOL* (R)	Isopropyl alcohol	400 ppm / 980 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ISOPROPANOL* (R)	Isopropyl alcohol	400 ppm / 980 mg/m3	1225 mg/m3 / 500 ppm	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	n-propyl acetate	n-Propyl acetate	200 ppm / 840 mg/m3	Not Available	Not Available	Not Available

Dykem® Remover & Prep (Aerosol)

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	n-propyl acetate	n-Propyl acetate	200 ppm / 840 mg/m3	1050 mg/m3 / 250 ppm	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	ETHANOL(R)	Ethyl alcohol (Ethanol)	1000 ppm / 1900 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ETHANOL(R)	Ethyl alcohol	1000 ppm / 1900 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
ACETONE* (R)	Not Available	Not Available	Not Available
ISOPROPANOL*(R)	400 ppm	2000* ppm	12000** ppm
n-propyl acetate	250 ppm	1,300 ppm	8000* ppm
ETHANOL(R)	Not Available	Not Available	15000* ppm

Ingredient	Original IDLH	Revised IDLH
ACETONE* (R)	2,500 ppm	Not Available
ISOPROPANOL*(R)	Not Available	Not Available
n-propyl acetate	1,700 ppm	Not Available
ETHANOL(R)	Not Available	Not Available
LPG (liquefied petroleum gas) sweetened	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.									
	General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.									
	<table><tr><td>Type of Contaminant:</td><td>Speed:</td></tr><tr><td>aerosols, (released at low velocity into zone of active generation)</td><td>0.5-1 m/s</td></tr><tr><td>direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)</td><td>1-2.5 m/s (200-500 f/min.)</td></tr></table>	Type of Contaminant:	Speed:	aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s	direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)			
	Type of Contaminant:	Speed:								
	aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s								
direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)									
Within each range the appropriate value depends on:										
<table><tr><td>Lower end of the range</td><td>Upper end of the range</td></tr><tr><td>1: Room air currents minimal or favourable to capture</td><td>1: Disturbing room air currents</td></tr><tr><td>2: Contaminants of low toxicity or of nuisance value only.</td><td>2: Contaminants of high toxicity</td></tr><tr><td>3: Intermittent, low production.</td><td>3: High production, heavy use</td></tr><tr><td>4: Large hood or large air mass in motion</td><td>4: Small hood-local control only</td></tr></table>	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood-local control only
Lower end of the range	Upper end of the range									
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents									
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity									
3: Intermittent, low production.	3: High production, heavy use									
4: Large hood or large air mass in motion	4: Small hood-local control only									
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.									
Individual protection measures, such as personal protective equipment	 									
Eye and face protection	▶ Safety glasses with side shields. ▶ Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent] ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.									
Skin protection	See Hand protection below									
Hands/feet protection	▶ No special equipment needed when handling small quantities. ▶ OTHERWISE: ▶ For potentially moderate exposures: ▶ Wear general protective gloves, eg. light weight rubber gloves. ▶ For potentially heavy exposures: ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.									
Body protection	See Other protection below									
Other protection	No special equipment needed when handling small quantities. OTHERWISE: ▶ Overalls. ▶ Skin cleansing cream.									

Continued...

- ▶ Eyewash unit.
- ▶ Do not spray on hot surfaces.

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Colourless		
Physical state	Liquified Gas	Relative density (Water = 1)	0.75-0.85
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	465
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	<20.5
Initial boiling point and boiling range (°C)	56.1	Molecular weight (g/mol)	Not Available
Flash point (°C)	-20	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	21.2	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.7	Volatile Component (%vol)	100
Vapour pressure (kPa)	24 @ 20 C	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC %	45.6%
Heat of Combustion (kJ/g)	>30	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▶ Elevated temperatures. ▶ Presence of open flame. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	There is sufficient evidence to classify this material as toxic to specific organs through single exposure
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.																											
Ingestion	Considered an unlikely route of entry in commercial/industrial environments																											
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.																											
Eye	This material causes serious eye irritation.																											
Chronic	Main route of exposure to the gas in the workplace is by inhalation.																											
Dykem® Remover & Prep (Aerosol)	<table><tr><th>TOXICITY</th><th>IRRITATION</th></tr><tr><td>Not Available</td><td>Not Available</td></tr></table>	TOXICITY	IRRITATION	Not Available	Not Available																							
TOXICITY	IRRITATION																											
Not Available	Not Available																											
ACETONE* (R)	<table><tr><th>TOXICITY</th><th>IRRITATION</th></tr><tr><td>Dermal (rabbit) LD50: 20000 mg/kg^[2]</td><td>Eye (Human): 186300ppm - Mild</td></tr><tr><td>Inhalation (Mouse) LC50: 44 mg/L4h^[2]</td><td>Eye (Human): 500ppm</td></tr><tr><td>Oral (Rat) LD50: 5800 mg/kg^[2]</td><td>Eye (Rodent - rabbit): 10uL - Mild</td></tr><tr><td></td><td>Eye (Rodent - rabbit): 20mg - Severe</td></tr><tr><td></td><td>Eye (Rodent - rabbit): 20mg/24H - Moderate</td></tr><tr><td></td><td>Eye: adverse effect observed (irritating)^[1]</td></tr><tr><td></td><td>Skin (Rodent - rabbit): 395mg - Mild</td></tr><tr><td></td><td>Skin (Rodent - rabbit): 500mg/24H - Mild</td></tr><tr><td></td><td>Skin: no adverse effect observed (not irritating)^[1]</td></tr></table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: 20000 mg/kg ^[2]	Eye (Human): 186300ppm - Mild	Inhalation (Mouse) LC50: 44 mg/L4h ^[2]	Eye (Human): 500ppm	Oral (Rat) LD50: 5800 mg/kg ^[2]	Eye (Rodent - rabbit): 10uL - Mild		Eye (Rodent - rabbit): 20mg - Severe		Eye (Rodent - rabbit): 20mg/24H - Moderate		Eye: adverse effect observed (irritating) ^[1]		Skin (Rodent - rabbit): 395mg - Mild		Skin (Rodent - rabbit): 500mg/24H - Mild		Skin: no adverse effect observed (not irritating) ^[1]							
TOXICITY	IRRITATION																											
Dermal (rabbit) LD50: 20000 mg/kg ^[2]	Eye (Human): 186300ppm - Mild																											
Inhalation (Mouse) LC50: 44 mg/L4h ^[2]	Eye (Human): 500ppm																											
Oral (Rat) LD50: 5800 mg/kg ^[2]	Eye (Rodent - rabbit): 10uL - Mild																											
	Eye (Rodent - rabbit): 20mg - Severe																											
	Eye (Rodent - rabbit): 20mg/24H - Moderate																											
	Eye: adverse effect observed (irritating) ^[1]																											
	Skin (Rodent - rabbit): 395mg - Mild																											
	Skin (Rodent - rabbit): 500mg/24H - Mild																											
	Skin: no adverse effect observed (not irritating) ^[1]																											
ISOPROPANOL*(R)	<table><tr><th>TOXICITY</th><th>IRRITATION</th></tr><tr><td>Dermal (rabbit) LD50: 12800 mg/kg^[2]</td><td>Eye (Rodent - rabbit): 100mg - Severe</td></tr><tr><td>Inhalation (Mouse) LC50: 53 mg/L4h^[2]</td><td>Eye (Rodent - rabbit): 100mg/24H - Moderate</td></tr><tr><td>Oral (Mouse) LD50; 3600 mg/kg^[2]</td><td>Eye (Rodent - rabbit): 10mg - Moderate</td></tr><tr><td></td><td>Eye: adverse effect observed (irritating)^[1]</td></tr><tr><td></td><td>Skin (Rodent - rabbit): 500mg - Mild</td></tr><tr><td></td><td>Skin: no adverse effect observed (not irritating)^[1]</td></tr></table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: 12800 mg/kg ^[2]	Eye (Rodent - rabbit): 100mg - Severe	Inhalation (Mouse) LC50: 53 mg/L4h ^[2]	Eye (Rodent - rabbit): 100mg/24H - Moderate	Oral (Mouse) LD50; 3600 mg/kg ^[2]	Eye (Rodent - rabbit): 10mg - Moderate		Eye: adverse effect observed (irritating) ^[1]		Skin (Rodent - rabbit): 500mg - Mild		Skin: no adverse effect observed (not irritating) ^[1]													
TOXICITY	IRRITATION																											
Dermal (rabbit) LD50: 12800 mg/kg ^[2]	Eye (Rodent - rabbit): 100mg - Severe																											
Inhalation (Mouse) LC50: 53 mg/L4h ^[2]	Eye (Rodent - rabbit): 100mg/24H - Moderate																											
Oral (Mouse) LD50; 3600 mg/kg ^[2]	Eye (Rodent - rabbit): 10mg - Moderate																											
	Eye: adverse effect observed (irritating) ^[1]																											
	Skin (Rodent - rabbit): 500mg - Mild																											
	Skin: no adverse effect observed (not irritating) ^[1]																											
n-propyl acetate	<table><tr><th>TOXICITY</th><th>IRRITATION</th></tr><tr><td>Dermal (Guinea Pig) LD50: >8880 mg/kg^[2]</td><td>Eye (Rodent - rabbit): 500mg/24H - Mild</td></tr><tr><td>Inhalation (Rat) LC50: ~32 mg/l4h^[1]</td><td>Eye: adverse effect observed (irritating)^[1]</td></tr><tr><td>Oral (Rabbit) LD50; 6640 mg/kg^[2]</td><td>Skin (Rodent - rabbit): 500mg - Mild</td></tr><tr><td></td><td>Skin: no adverse effect observed (not irritating)^[1]</td></tr></table>	TOXICITY	IRRITATION	Dermal (Guinea Pig) LD50: >8880 mg/kg ^[2]	Eye (Rodent - rabbit): 500mg/24H - Mild	Inhalation (Rat) LC50: ~32 mg/l4h ^[1]	Eye: adverse effect observed (irritating) ^[1]	Oral (Rabbit) LD50; 6640 mg/kg ^[2]	Skin (Rodent - rabbit): 500mg - Mild		Skin: no adverse effect observed (not irritating) ^[1]																	
TOXICITY	IRRITATION																											
Dermal (Guinea Pig) LD50: >8880 mg/kg ^[2]	Eye (Rodent - rabbit): 500mg/24H - Mild																											
Inhalation (Rat) LC50: ~32 mg/l4h ^[1]	Eye: adverse effect observed (irritating) ^[1]																											
Oral (Rabbit) LD50; 6640 mg/kg ^[2]	Skin (Rodent - rabbit): 500mg - Mild																											
	Skin: no adverse effect observed (not irritating) ^[1]																											
ETHANOL(R)	<table><tr><th>TOXICITY</th><th>IRRITATION</th></tr><tr><td>Dermal (rabbit) LD50: 17100 mg/kg^[1]</td><td>Eye (Rodent - rabbit): 0.1mL</td></tr><tr><td>Inhalation (Rat) LC50: 64000 ppm4h^[2]</td><td>Eye (Rodent - rabbit): 100mg/4S - Moderate</td></tr><tr><td>Oral (Rat) LD50: 7060 mg/kg^[2]</td><td>Eye (Rodent - rabbit): 100uL - Moderate</td></tr><tr><td></td><td>Eye (Rodent - rabbit): 500mg - Severe</td></tr><tr><td></td><td>Eye (Rodent - rabbit): 500mg/24H - Mild</td></tr><tr><td></td><td>Eye (Rodent - rabbit): 50pph/1H - Mild</td></tr><tr><td></td><td>Eye: adverse effect observed (irritating)^[1]</td></tr><tr><td></td><td>Eye: no adverse effect observed (not irritating)^[1]</td></tr><tr><td></td><td>Skin (Human): 70%/2D</td></tr><tr><td></td><td>Skin (Rodent - rabbit): 20mg/24H - Moderate</td></tr><tr><td></td><td>Skin (Rodent - rabbit): 400mg - Mild</td></tr><tr><td></td><td>Skin: no adverse effect observed (not irritating)^[1]</td></tr></table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: 17100 mg/kg ^[1]	Eye (Rodent - rabbit): 0.1mL	Inhalation (Rat) LC50: 64000 ppm4h ^[2]	Eye (Rodent - rabbit): 100mg/4S - Moderate	Oral (Rat) LD50: 7060 mg/kg ^[2]	Eye (Rodent - rabbit): 100uL - Moderate		Eye (Rodent - rabbit): 500mg - Severe		Eye (Rodent - rabbit): 500mg/24H - Mild		Eye (Rodent - rabbit): 50pph/1H - Mild		Eye: adverse effect observed (irritating) ^[1]		Eye: no adverse effect observed (not irritating) ^[1]		Skin (Human): 70%/2D		Skin (Rodent - rabbit): 20mg/24H - Moderate		Skin (Rodent - rabbit): 400mg - Mild		Skin: no adverse effect observed (not irritating) ^[1]	
TOXICITY	IRRITATION																											
Dermal (rabbit) LD50: 17100 mg/kg ^[1]	Eye (Rodent - rabbit): 0.1mL																											
Inhalation (Rat) LC50: 64000 ppm4h ^[2]	Eye (Rodent - rabbit): 100mg/4S - Moderate																											
Oral (Rat) LD50: 7060 mg/kg ^[2]	Eye (Rodent - rabbit): 100uL - Moderate																											
	Eye (Rodent - rabbit): 500mg - Severe																											
	Eye (Rodent - rabbit): 500mg/24H - Mild																											
	Eye (Rodent - rabbit): 50pph/1H - Mild																											
	Eye: adverse effect observed (irritating) ^[1]																											
	Eye: no adverse effect observed (not irritating) ^[1]																											
	Skin (Human): 70%/2D																											
	Skin (Rodent - rabbit): 20mg/24H - Moderate																											
	Skin (Rodent - rabbit): 400mg - Mild																											
	Skin: no adverse effect observed (not irritating) ^[1]																											
LPG (liquefied petroleum gas) sweetened	<table><tr><th>TOXICITY</th><th>IRRITATION</th></tr><tr><td>Inhalation (Rat) LC50: 658 mg/l4h^[2]</td><td>Not Available</td></tr></table>	TOXICITY	IRRITATION	Inhalation (Rat) LC50: 658 mg/l4h ^[2]	Not Available																							
TOXICITY	IRRITATION																											
Inhalation (Rat) LC50: 658 mg/l4h ^[2]	Not Available																											

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity					
Dykem® Remover & Prep (Aerosol)	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
ACETONE* (R)	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	5600-10000mg/L	4
	EC50	48h	Crustacea	6098.4mg/L	5
	EC50	96h	Algae or other aquatic plants	9.873-27.684mg/l	4
	NOEC(ECx)	12h	Fish	0.001mg/L	4
	LC50	96h	Fish	3744.6-5000.7mg/L	4
ISOPROPANOL*(R)	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>1000mg/l	1
	EC50	48h	Crustacea	7550mg/l	4
	EC50	96h	Algae or other aquatic plants	>1000mg/l	1
	EC50(ECx)	24h	Algae or other aquatic plants	0.011mg/L	4
	LC50	96h	Fish	>1400mg/L	4
n-propyl acetate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	672mg/l	2
	EC50	48h	Crustacea	91.5mg/l	2
	NOEC(ECx)	48h	Crustacea	32.1mg/l	2
ETHANOL(R)	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	275mg/l	2
	EC50	48h	Crustacea	2mg/L	4
	EC50	96h	Algae or other aquatic plants	<0.001mg/L	4
	EC50(ECx)	96h	Algae or other aquatic plants	<0.001mg/L	4
	LC50	96h	Fish	42mg/L	4
LPG (liquefied petroleum gas) sweetened	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	96h	Algae or other aquatic plants	7.71mg/l	2
	EC50(ECx)	96h	Algae or other aquatic plants	7.71mg/l	2
Legend:	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	24.11mg/l	2
Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

DO NOT discharge into sewer or waterways.

Persistence and degradability		
Ingredient	Persistence: Water/Soil	Persistence: Air
ACETONE* (R)	LOW (Half-life = 14 days)	MEDIUM (Half-life = 116.25 days)
ISOPROPANOL*(R)	LOW (Half-life = 14 days)	LOW (Half-life = 3 days)
n-propyl acetate	LOW	LOW
ETHANOL(R)	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)

Bioaccumulative potential	
Ingredient	Bioaccumulation
ACETONE* (R)	LOW (BCF = 0.69)

Ingredient	Bioaccumulation
ISOPROPANOL*(R)	LOW (LogKOW = 0.05)
n-propyl acetate	LOW (BCF = 5.1)
ETHANOL(R)	LOW (LogKOW = -0.31)
LPG (liquefied petroleum gas) sweetened	LOW (LogKOW = 3.39)

Mobility in soil

Ingredient	Mobility
ACETONE* (R)	HIGH (Log KOC = 1.981)
ISOPROPANOL*(R)	HIGH (Log KOC = 1.06)
n-propyl acetate	LOW (Log KOC = 11.31)
ETHANOL(R)	HIGH (Log KOC = 1)

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	- Consult State Land Waste Management Authority for disposal. - Discharge contents of damaged aerosol cans at an approved site. - Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans. - Bury residues and emptied aerosol cans at an approved site.
------------------------------	---

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO

Shipping container, transport vehicle placarding, and labeling may vary from the below information. This depends on the quantity shipped, the applicability of excepted quantity requirements, limited quantity requirements, and/or special provisions according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT)

14.1. UN number or ID number	1950	
14.2. UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)	
14.3. Transport hazard class(es)	Class	2.1
	Subsidiary Hazard	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Hazard Label	2.1
	Special provisions	N82

Air transport (ICAO-IATA / DGR)

14.1. UN number	1950	
14.2. UN proper shipping name	Aerosols, flammable	
14.3. Transport hazard class(es)	ICAO/IATA Class	2.1
	ICAO / IATA Subsidiary Hazard	Not Applicable
	ERG Code	10L
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Special provisions	A145 A167 A802
	Cargo Only Packing Instructions	203
	Cargo Only Maximum Qty / Pack	150 kg
	Passenger and Cargo Packing Instructions	203
	Passenger and Cargo Maximum Qty / Pack	75 kg

	Passenger and Cargo Limited Quantity Packing Instructions	Y203
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1950	
14.2. UN proper shipping name	AEROSOLS	
14.3. Transport hazard class(es)	IMDG Class	2.1
	IMDG Subsidiary Hazard	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number	F-D, S-U
	Special provisions	63 190 277 327 344 381 959
	Limited Quantities	1000 ml

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code
Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ACETONE* (R)	Not Available
ISOPROPANOL*(R)	Not Available
n-propyl acetate	Not Available
ETHANOL(R)	Not Available
LPG (liquefied petroleum gas) sweetened	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
ACETONE* (R)	Not Available
ISOPROPANOL*(R)	Not Available
n-propyl acetate	Not Available
ETHANOL(R)	Not Available
LPG (liquefied petroleum gas) sweetened	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

ACETONE* (R) is found on the following regulatory lists
US - Massachusetts - Right To Know Listed Chemicals
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Flammables
US - New Jersey Right to Know Hazardous Substances
US - Pennsylvania - Hazardous Substance List
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US DOE Temporary Emergency Exposure Limits (TEELs)
US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals
US EPA Integrated Risk Information System (IRIS)
US EPA Pesticide Chemical Search - Antimicrobial
US EPA Pesticide Chemical Search - Conventional Chemical
US New York City Community Right-to-Know: List of Hazardous Substances
US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Section 4/12 (b) - Sunset Dates/Status
ISOPROPANOL*(R) is found on the following regulatory lists
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic
US - Massachusetts - Right To Know Listed Chemicals
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Flammables
US - New Jersey Right to Know Hazardous Substances
US - Pennsylvania - Hazardous Substance List
US DOE Temporary Emergency Exposure Limits (TEELs)
US EPA Pesticide Chemical Search - Antimicrobial
US EPA Pesticide Chemical Search - Biopesticides
US EPA Pesticide Chemical Search - Conventional Chemical
US EPCRA Section 313 Chemical List
US New York City Community Right-to-Know: List of Hazardous Substances

US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Section 4/12 (b) - Sunset Dates/Status

n-propyl acetate is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Flammables
US - New Jersey Right to Know Hazardous Substances
US - Pennsylvania - Hazardous Substance List
US DOE Temporary Emergency Exposure Limits (TEELs)
US New York City Community Right-to-Know: List of Hazardous Substances
US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

ETHANOL(R) is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Flammables
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Mutagens
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Teratogens
US - New Jersey Right to Know Hazardous Substances
US - Pennsylvania - Hazardous Substance List
US DOE Temporary Emergency Exposure Limits (TEELs)
US EPA Pesticide Chemical Search - Antimicrobial
US EPA Pesticide Chemical Search - Biopesticides
US EPA Pesticide Chemical Search - Conventional Chemical
US New York City Community Right-to-Know: List of Hazardous Substances
US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

LPG (liquefied petroleum gas) sweetened is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	Yes
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Continued...

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
ACETONE* (R)	5000	2270

US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372) This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):		
CAS No	%[weight]	Name
67-63-0	1-3	ISOPROPANOL*(R)
<i>This information must be included in all SDSs that are copied and distributed for this material.</i>		

Additional Federal Regulatory Information
Not Applicable

State Regulations

US. California Proposition 65 None Reported
Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ACETONE* (R); ISOPROPANOL*(R); n-propyl acetate; ETHANOL(R); LPG (liquefied petroleum gas) sweetened)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (LPG (liquefied petroleum gas) sweetened)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (ACETONE* (R); ISOPROPANOL*(R); n-propyl acetate; ETHANOL(R); LPG (liquefied petroleum gas) sweetened)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	03/10/2025
Initial Date	10/12/2023

Other information
The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.