

SAFETY DATA SHEET

Issuing Date Nov.19-2015 Revision Date Nov. 19-2015 Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name HUB-MARK PAINT MARKER - MOST COLORS

Other means of identification 064-003-260 Black

064-003-261 Blue

Product Code(s) 064-003-262 Green 064-003-263 Red

064-003-263 Red 064-003-264 Yellow 064-003-265 White 064-003-266 Orange

UN-Number UN1210

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Solvent based marker

Uses advised against Not for use on skin. Keep away from children.

Supplier's details

Supplier Address HUB Industrial Supply 371 SW Ring Ct. Lake City FL 32025 800.743.9401

Emergency telephone number

Chemical Emergency Phone Number

24-hour Emergency Phone: Infotrac 1-800-535-5053 (USA & Canada), 1-352-323-3500 (International)

2. HAZARDS IDENTIFICATION

Classification

This product is an article as defined by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200). No exposure to hazardous chemicals is expected to occur during intended product use. Misuse of the product may result in exposure to hazardous chemicals. The classification below applies to the liquid ink in this marker.

This product is not a toxic or hazardous substance as defined by 16 CRF 1500.3 of the Federal Hazardous Substances Act (FHSA) and as such does not require acute or chronic hazard labeling. Reviews were conducted using guidelines set forth by the CPSC (Consumer Product Safety Commission). Inks are certified as compliant under ASTM D-4236

HUB-Mark Markers Revision Date Nov.19-2015

GHS Label elements, including precautionary statements

Emergency Overview

Keep away from children.

The product contains no substances which at their given concentration are considered to be hazardous to health

Appearance Varies Physical State Liquid. Odor Alcohol

Precautionary Statements

Prevention

None

General Advice

None

Storage

None

Disposal

None

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Chemical Name	CAS-No	Weight %	Trade secret
Propyl alcohol	71-23-8	30-70	*
Titanium dioxide	13463-67-7	10-20	*
Pigment Yellow 83	5567-15-7	0-10	*
C.I. Pigment red 3	2425-85-6	0-7	*
Carbon black	1333-86-4	0-5	*
C.I. Pigment Blue 15	147-14-8	0-5	*
Ci 51319	6358-30-1	0-3	*
Silicon dioxide	7631-86-9	1-3	*
Silica, amorphous, fumed, crystal-free	112945-52-5	0-2	*
Propylene glycol monomethyl ether acetate	108-65-6	0.1-1.0	*
n-Butyl acetate	123-86-4	0.1-1.0	*
Dipropylene glycol monomethyl ether	34590-94-8	0.1-1.0	*
Copper, [29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]-, chlorinated	68987-63-3	0.1-1.0	*
Copper	7440-50-8	0.1-1.0	*
n-Butyl alcohol	71-36-3	<0.1	*
Sodium bisulfite	7631-90-5	<0.1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

HUB-Mark Markers Revision Date Nov. 19-2015

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice Under normal conditions of use first aid is not required.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or Poison Control Center

immediately.

Skin Contact Wash skin with soap and water. Get medical attention if irritation develops and persists.

Inhalation If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects None known

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media None.

Specific Hazards Arising from the Chemical

The ink contained in this product is flammable but not readily ignited.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition.

Environmental Precautions

Environmental PrecautionsAvoid release to the environment. Dispose of contents/container to an approved waste

disposal plant. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment None required.

Methods for Cleaning UpPick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Keep away from open flames, hot surfaces and sources of ignition.

Conditions for safe storage, including any incompatibilities

Storage Store in a well-ventilated place. Keep cool.

Incompatible ProductsNone known based on information supplied.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines This product does not contain any hazardous materials with occupational exposure limits

established by the region specific regulatory bodies.

Appropriate engineering controls

Engineering Measures None under normal use conditions.

Individual protection measures, such as personal protective equipment

Eye/Face ProtectionNo protective equipment is needed under normal use conditions.Skin and Body ProtectionNo protective equipment is needed under normal use conditions.Respiratory ProtectionNo protective equipment is needed under normal use conditions.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid Appearance Varies.

Odor Alcohol Odor Threshold No information available

Property Remarks/ - Method Values No data available None known Hq Melting Point/Range No data available None known **Boiling Point/Boiling Range** 96 °C / 205 °F (Liquid Ink only) 23 °C / 73 °F **Flash Point** (Liquid Ink only) **Evaporation rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limits in Air upper flammability limit 13.5% lower flammability limit 2.1% **Vapor Pressure** No data available None known **Vapor Density** No data available None known None known **Specific Gravity** No data available Water Solubility No data available None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition Temperature** No data available None known **Decomposition Temperature** No data available None known **Viscosity** No data available None known Flammable Properties Flammable. **Explosive Properties** No data available **Oxidizing Properties** No data available Other information

VOC Content (%) No data available

HUB Mark Markers Revision Date Nov. 19-2015

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

InhalationNone under normal use conditionsEye ContactNone under normal use conditions.Skin ContactNone under normal use conditions.IngestionNone under normal use conditions.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Propyl alcohol	= 1870 mg/kg (Rat)	= 4049 mg/kg (Rabbit)	> 13548 ppm (Rat) 4 h
Titanium dioxide	> 10000 mg/kg (Rat)	-	> 6820 mg/m ³
Carbon black	-	> 3 g/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms None under normal use.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization Mutagenic EffectsNo information available.
No information available.

CarcinogenicityThis product contains titanium dioxide which is classified as a possible carcinogen when present as respirable dust. This is not relevant for this product since it is a liquid. This

product contains carbon black which is classified as a possible carcinogen when present as respirable dust. This is not relevant for this product since it is not in a respirable form.

HUB-Mark Markers Revision Date Nov. 19-2015

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
C.I. Pigment red 3		Group 3		
Carbon black	A3	Group 2B		X
Silicon dioxide		Group 3		
Silica, amorphous, fumed, crystal-free		Group 3		
Sodium bisulfite		Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 1747 mg/kg; Acute toxicity estimate **LD50 Dermal** 3787 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

Not Applicable

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Propyl alcohol		LC50 96 h: = 4480 mg/L	EC50 = 17700 mg/L 5 min	EC50 48 h: = 3642 mg/L
71-23-8		flow-through (Pimephales	EC50 = 45000 mg/L 5 h	(Daphnia magna) EC50 48
		promelas)	EC50 = 8686 mg/L 15 min	h: 3339 - 3977 mg/L Static
			EC50 = 980 mg/L 12 h	(Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Propyl alcohol	0.34
C.I. Pigment Blue 15	6.6
Propylene glycol monomethyl ether acetate	0.43
n-Butyl acetate	1.81
Dipropylene glycol monomethyl ether	-0.064
n-Butyl alcohol	0.785

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated Packaging Not Applicable

HUB Mark Markers Revision Date Nov. 19-2015

14. TRANSPORT INFORMATION

DOT

UN-Number UN1210 **Proper shipping name** Printing ink

Hazard Class 3
Packing Group III

Description UN1210, Printing ink, 3, III, Limited Quantity

Emergency Response Guide 129

Number

<u>TDG</u>

UN-Number UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III

Description UN1210, Printing ink, 3, III, Limited Quantity

MEX

UN-Number UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III

Description UN1210, Printing ink, 3, III, Limited Quantity

ICAO

UN-Number UN1210
Proper shipping name Printing ink

Hazard Class 3
Packing Group III

Description UN1210, Printing ink, 3, III, Limited Quantity

<u>IATA</u>

UN-Number UN1210
Proper Shipping Name Printing ink

Hazard Class3Packing GroupIIIERG Code3L

Description UN1210, Printing ink, 3, III, Limited Quantity

IMDG/IMO

UN-Number UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III
EmS No. F-E, S-D

Description UN1210, Printing ink, 3, III, (23°C c.c.), Limited Quantity

RID

UN-Number UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III
Classification Code F1

Description UN1210, Printing ink, 3, III, Limited Quantity

HUB-Mark Markers

Revision Date Nov. 19-2015

ADR

UN-Number UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III
Classification Code F1
Tunnel Restriction Code (D/E)

Description UN1210, Printing ink, 3, III, (D/E), Limited Quantity

ADN

Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III
Classification Code F1
Special Provisions 163, 640E

Description UN1210, Printing ink, 3, III, Limited Quantity

Limited Quantity 5 L Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health HazardNoChronic Health HazardNoFire HazardYesSudden Release of Pressure HazardNoReactive HazardNo

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
C.I. Pigment Blue 15		X		
n-Butyl acetate	5000 lb			X
Copper, [29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]-, chlorinated		Х		
Copper		X	X	
Sodium bisulfite	5000 lb			X

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

HUB-Mark Markers Revision Date Nov. 19-2015

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances	RQ
		RQs	
n-Butyl acetate	5000 lb		RQ 5000 lb final RQ
-			RQ 2270 kg final RQ
Copper	5000 lb		RQ 5000 lb final RQ
			RQ 2270 kg final RQ
n-Butyl alcohol	5000 lb		RQ 5000 lb final RQ
·			RQ 2270 kg final RQ
Sodium bisulfite	5000 lb		RQ 5000 lb final RQ
			RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

The classification listed below only applies to respirable Titanium dioxide and respirable carbon black. This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen
Carbon black	1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

This product does not contain any substances above threshold limits that are regulated by state right-to-know.

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION					
NFPA	Health Hazard 0	Flammability	2	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 0	Flammability	2	Physical Hazard 0	Personal Protection X

Prepared By HUB Industrial Supply

371 Ring Ct

Lake City FL 32025 1-800-743-9401 Nov. 19-2015

Issuing DateNov. 19-2015Revision DateNove> 19-2015Revision NoteInitial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet
