Safety Data Sheet

Date of issue: 11/03/2025 Revised On 11/03/2025

1 Identification of the substance and manufacturer

Trade name: TRU-GALV ZINC RICH

Other means of identification

065-017-015 Product code:

Article category Recommended use: Paint and coatings application.

Any that differs from the recommended use. HUB Industrial Supply Uses advised against:

Manufacturer/Supplier:

371 SW Ring Court Lake City, FL 32025 phone: 800-743-9401 1-800-424-9300

Emergency telephone number:

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Skin irritation 2 H315 Causes skin irritation.

Suspected of damaging fertility or the unborn child. H361 Reproductive toxicity 2

Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**





GHS02 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid breathing fume/mist/vapors/spray. Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Wear protective gloves.

If on skin: Wash with plenty of water.
If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions

Gilonnour Booonphon.		This product is a mixture of the substances holes below with horniazarasas additions.	
Dangerous components:			
108-88-3	Toluene		≥20-≤25%
74-98-6	propane		10-15%
106-97-8	n-butane		5-10%
64742-47-8	Mineral Spirits		1-5%
67-63-0	Isopropyl Alcohol		1-5%

4 First-aid measures

After swallowing:

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects: Dizziness

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Date of issue: 11/03/2025 Revised On 11/03/2025

Trade name: COLD GALV

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Methods and material for Use respiratory protective device against the effects of fumes/dust/aerosol.

containment and cleaning up: Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas. Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

Long-term value: 20 ppm TLV (USA)

BEI, OTO, A4

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

(EX)

67-63-0 Isopropyl Alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm

Short-term value: 1225 mg/m³, 500 ppm REL (USA)

Long-term value: 980 mg/m³, 400 ppm

TLV (USA) Short-term value: 984 mg/m³, 400 ppm Long-term value: 491 mg/m³, 200 ppm

BEI, A4

Ingredients with biological limit values:

108-88-3 Toluene

BEI (USA) 0.02 mg/L Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine

Time: end of shift Parameter: o-Cresol with hydrolysis (background)

67-63-0 Isopropyl Alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

Hygienic protection:

Immediately remove all soiled and contaminated clothing.

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Date of issue: 11/03/2025 Revised On 11/03/2025

Trade name: COLD GALV

Wash hands after use.

Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Physical state Aerosol Odor: Aromatic Odor threshold: Not determined. Melting point/Melting range Undetermined. -44 °C (-47.2 °F) Boiling point: Flammability: Extremely flammable.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % -19 °C (-2.2 °F) Upper Explosion Limit: Flash point: Flammability (solid, gas): Extremely flammable. Decomposition temperature: Not determined. pH-value: Viscosity: Not determined. Not determined. Solubility: Not determined. Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Particle characteristics Not applicable.

Appearance: Aerosol.

Ignition temperature: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 Isopropyl Alcohol

Oral LD50 4,570 mg/kg (rat) Dermal LD50 13,400 mg/kg (rab) Inhalative LC50/4 h 30 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: Irritant to skin and mucous membranes.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), Other information:

perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

No further relevant information available.

Bioaccumulative potential: Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

(Contd. on page 4)

Safety Data Sheet

Date of issue: 11/03/2025 Revised On 11/03/2025

Trade name: COLD GALV

Recommendation: Completely empty cans should be recycled. (Contd. of page 3)

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable

ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

Transport hazard class(es):

Class 2.1 Gases

Marine pollutant: Special marking (IATA): Symbol (fish and tree)

Packaging Group:
Special precautions for user:

EMS Number:

Warning: Gases F-D,S-U UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS UN "Model Regulation":

15 Regulatory information

SARA Section 355 (extremely hazardous substances):			
None of the ingredients in this product are listed.			
SARA Section 313 (Specific toxic chemical listings):			
7440-66-6 zinc powder			
108-88-3 Toluene			
67-63-0 Isopropyl Alcohol			
1314-13-2 zinc oxide			

Toxic Substances Control Act

(TSCA): All ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

7440-66-6 zinc powder D, I, II 1314-13-2 zinc oxide D, I, II

16 Other information

Contact: Regulatory Affairs