

# SAFETY DATA SHEET

## Section 1. Identification

**GHS product identifier** : 100P Industrial Paint Marker, 100P Fine Line, 130P Industrial Paint Marker

**Other means of identification** :

**Product type** : Paint Marker

**Product code** : **100P**: #10201 Black, #10202 Blue, #10203 Green, #10204 Red, #10205 White, #10206 Yellow, #10207 Orange, #10209 Bright Green, #10210 Silver, #10211 Pink, #10212 Violet, #10213 Light Blue, #10214 Gold, #10215 Brown  
**100P Fine Line**: #10201FL Black, #10202FL Blue, #10203FL Green, #10204FL Red, #10205FL White, #10206FL Yellow, #10207FL Orange, #10209FL Bright Green, #10210FL Silver, #10211FL Pink, #10212FL Violet, #10213FL Light Blue, #10214FL Gold, #10215FL Brown  
**130P**: #13001 Black, #13002 Blue, #13003 Green, #13004 Red, #13005 White, #13006 Yellow, #13007 Orange, #13008 Light Blue, #13009 Bright Green, #13010 Silver, #13011 Pink, #13012 Violet, #13014 Gold, #13015 Brown

**Identified uses** : Marking on various surfaces

**Supplier's details** : U-Mark, Inc.  
 102 Iowa Ave.  
 Belleville, IL  
 TEL: 618-235-7500

**Emergency telephone number (with hours of operation)** : 24-hour Emergency Phone: Infotrac 1-800-535-5053 (USA & Canada)  
 1-352-323-3500 (International)

## Section 2. Hazards identification

**OSHA/HCS status** : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

**This SDS reflects the health, physical and environmental hazards of the liquid ink contained within the pen/ marker. Because of the nature of the finished product i.e. the fact that the ink is held internally within the pen/ marker inside a closed (sealed) container, and given that the liquid is present in a small quantity and is released in very small amounts during normal use, the user of the product and/or the reader of this SDS should consider the potential exposure to the ink to be minimal and controlled during the normal use of the product. Refer to relevant sections of the SDS (7 and 13) for additional information on handling and disposal considerations. To avoid any potential hazard and to minimize the risk of exposure, it is important that the user of the product does NOT open, heat, burn or expose it to a source of intense heat, as this could release the ink.**

**Classification of the substance or mixture** : Not classified.



## Section 2. Hazards identification

### GHS label elements

- Signal word** : No signal word.  
**Hazard statements** : No known significant effects or critical hazards.  
**Precautionary statements**  
**Prevention** : Not applicable.  
**Response** : Not applicable.  
**Storage** : Not applicable.  
**Disposal** : Not applicable.  
**Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture  
**Other means of identification** : Not available.

### CAS number/other identifiers

- CAS number** : Not applicable.  
**Product code** : Not available.

Ingredient name	%	CAS number
Xylene	30 - 60	1330-20-7
m-Xylene	30 - 60	108-38-3
Titanium dioxide	10 - 30	13463-67-7
p-Xylene	10 - 30	106-42-3
Ethylbenzene	5 - 10	100-41-4
o-Xylene	5 - 10	95-47-6
Carbon black	5 - 10	1333-86-4
Toluene	0.1 - 1	108-88-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

**Under normal conditions of use first aid is not required.**

- Eye contact** : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or Poison Control Center immediately.  
**Inhalation** : If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.  
**Skin contact** : Wash skin with soap and water. Get medical attention if irritation develops and persists.  
**Ingestion** : IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

## Section 4. First aid measures

### Over-exposure signs/symptoms

- Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically.  
**Specific treatments** : No specific treatment.  
**Protection of first-aiders** : No special measures required.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.  
**Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : Not applicable.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
sulfur oxides  
halogenated compounds  
metal oxide/oxides

**Special protective actions for fire-fighters** : No special measures are required.

**Special protective equipment for fire-fighters** : No special protection is required.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Provide adequate ventilation.  
**For emergency responders** : Not applicable.

**Environmental precautions** : Not applicable.

### Methods and materials for containment and cleaning up

- Spill** : Not applicable.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).  
**Advice on general occupational hygiene** : Workers should wash hands and face before eating, drinking and smoking.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
<p>Xylene</p> <p>m-Xylene</p> <p>Titanium dioxide</p> <p>p-Xylene</p>	<p><b>ACGIH TLV (United States, 4/2014).</b>            STEL: 651 mg/m<sup>3</sup> 15 minutes.            STEL: 150 ppm 15 minutes.            TWA: 434 mg/m<sup>3</sup> 8 hours.            TWA: 100 ppm 8 hours.</p> <p><b>OSHA PEL (United States, 2/2013).</b>            TWA: 100 ppm 8 hours.            TWA: 435 mg/m<sup>3</sup> 8 hours.</p> <p><b>ACGIH TLV (United States, 2/2010).</b>            STEL: 651 mg/m<sup>3</sup> 15 minutes.            STEL: 150 ppm 15 minutes.            TWA: 434 mg/m<sup>3</sup> 8 hours.            TWA: 100 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 6/2009).</b>            STEL: 655 mg/m<sup>3</sup> 15 minutes.            STEL: 150 ppm 15 minutes.            TWA: 435 mg/m<sup>3</sup> 10 hours.            TWA: 100 ppm 10 hours.</p> <p><b>OSHA PEL (United States, 6/2010).</b>            TWA: 435 mg/m<sup>3</sup> 8 hours.            TWA: 100 ppm 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2005).</b>            STEL: 651 mg/m<sup>3</sup> 15 minutes. Form: All forms.            STEL: 150 ppm 15 minutes. Form: All forms.            TWA: 434 mg/m<sup>3</sup> 8 hours. Form: All forms.            TWA: 100 ppm 8 hours. Form: All forms.</p> <p><b>NIOSH REL (United States, 12/2001).</b>            STEL: 655 mg/m<sup>3</sup> 15 minutes. Form: All forms.            STEL: 150 ppm 15 minutes. Form: All forms.            TWA: 435 mg/m<sup>3</sup> 10 hours. Form: All forms.            TWA: 100 ppm 10 hours. Form: All forms.</p> <p><b>OSHA PEL (United States, 8/1997).</b>            TWA: 435 mg/m<sup>3</sup> 8 hours. Form: All forms.            TWA: 100 ppm 8 hours. Form: All forms.</p> <p><b>OSHA PEL (United States, 2/2013).</b>            TWA: 15 mg/m<sup>3</sup> 8 hours. Form: Total dust</p> <p><b>ACGIH TLV (United States, 4/2014).</b>            TWA: 10 mg/m<sup>3</sup> 8 hours.</p> <p><b>ACGIH TLV (United States, 2/2010).</b>            STEL: 651 mg/m<sup>3</sup> 15 minutes.            STEL: 150 ppm 15 minutes.            TWA: 434 mg/m<sup>3</sup> 8 hours.</p> <p><b>NIOSH REL (United States, 6/2009).</b>            STEL: 655 mg/m<sup>3</sup> 15 minutes.            STEL: 150 ppm 15 minutes.            TWA: 435 mg/m<sup>3</sup> 10 hours.            TWA: 100 ppm 10 hours.</p> <p><b>OSHA PEL (United States, 6/2010).</b>            TWA: 435 mg/m<sup>3</sup> 8 hours.</p>



## Section 8. Exposure controls/personal protection

Ethylbenzene	<p>TWA: 100 ppm 8 hours.  <b>ACGIH TLV (United States, 4/2014).</b>            TWA: 20 ppm 8 hours.  <b>NIOSH REL (United States, 10/2013).</b>            STEL: 545 mg/m<sup>3</sup> 15 minutes.            STEL: 125 ppm 15 minutes.            TWA: 435 mg/m<sup>3</sup> 10 hours.            TWA: 100 ppm 10 hours.  <b>OSHA PEL (United States, 2/2013).</b>            TWA: 435 mg/m<sup>3</sup> 8 hours.            TWA: 100 ppm 8 hours.</p>
o-Xylene	<p><b>ACGIH TLV (United States, 2/2010).</b>            STEL: 651 mg/m<sup>3</sup> 15 minutes.            STEL: 150 ppm 15 minutes.            TWA: 434 mg/m<sup>3</sup> 8 hours.            TWA: 100 ppm 8 hours.  <b>NIOSH REL (United States, 6/2009).</b>            STEL: 655 mg/m<sup>3</sup> 15 minutes.            STEL: 150 ppm 15 minutes.            TWA: 435 mg/m<sup>3</sup> 10 hours.            TWA: 100 ppm 10 hours.  <b>OSHA PEL (United States, 6/2010).</b>            TWA: 435 mg/m<sup>3</sup> 8 hours.            TWA: 100 ppm 8 hours.</p>
Carbon black	<p><b>ACGIH TLV (United States, 4/2014).</b>            TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction.  <b>NIOSH REL (United States, 10/2013).</b>            TWA: 3.5 mg/m<sup>3</sup> 10 hours.            TWA: 0.1 mg of PAHs/cm<sup>3</sup> 10 hours.  <b>OSHA PEL (United States, 2/2013).</b>            TWA: 3.5 mg/m<sup>3</sup> 8 hours.</p>
Toluene	<p><b>NIOSH REL (United States, 10/2013).</b>            STEL: 560 mg/m<sup>3</sup> 15 minutes.            STEL: 150 ppm 15 minutes.            TWA: 375 mg/m<sup>3</sup> 10 hours.            TWA: 100 ppm 10 hours.  <b>OSHA PEL Z2 (United States, 2/2013).</b>            AMP: 500 ppm 10 minutes.            CEIL: 300 ppm            TWA: 200 ppm 8 hours.  <b>ACGIH TLV (United States, 4/2014).</b>            TWA: 20 ppm 8 hours.</p>

**Appropriate engineering controls** : No special ventilation requirements.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

### Individual protection measures

**Hygiene measures** : Follow good industrial hygiene practice.

**Eye/face protection** : No special measures are required.

#### Skin protection

**Hand protection** : Not required for normal use of the pen/marker.

**Body protection** : Not required for normal use of the pen/marker.

**Other skin protection** : Not required for normal use of the pen/marker.

**Respiratory protection** : Not required for normal use of the pen/marker.



## Section 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	: Liquid. [in cylindrical marker]
<b>Color</b>	: Colored, opaque liquid.
<b>Odor</b>	: Hydrocarbon.
<b>Odor threshold</b>	: Not available.
<b>pH</b>	: Not available.
<b>Melting point</b>	: Not available.
<b>Boiling point</b>	: 119 to 207°C (246.2 to 404.6°F)
<b>Flash point</b>	: Closed cup: 24 to 29°C (75.2 to 84.2°F)
<b>Evaporation rate</b>	: Not available.
<b>Flammability (solid, gas)</b>	: Not available.
<b>Lower and upper explosive (flammable) limits</b>	: Lower: 1% Upper: 7%
<b>Vapor pressure</b>	: 0.67 to 0.93 kPa (5 to 7 mm Hg) [room temperature]
<b>Vapor density</b>	: >1 [Air = 1]
<b>Relative density</b>	: 0.9
<b>Solubility</b>	: Insoluble in the following materials: cold water and hot water.
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Not available.
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Not available.
<b>Volatility</b>	: 40 to 65% (v/v)

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame).
<b>Incompatible materials</b>	: Not applicable.
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.



## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
m-Xylene	LD50 Oral	Rat	4988 mg/kg	-
p-Xylene	LC50 Inhalation Gas.	Rat	4550 ppm	4 hours
	LD50 Oral	Rat	3910 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
o-Xylene	LD50 Oral	Rat	3567 mg/kg	-
Carbon black	LD50 Oral	Rat	>15400 mg/kg	-
Toluene	LC50 Inhalation Vapor	Rat	49 g/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	636 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 µL	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
m-Xylene	Skin - Moderate irritant	Rabbit	-	100%	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 10 µg	-
Titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 µg Intermittent	-
Ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Mild irritant	Rabbit	-	870 µg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Pig	-	24 hours 250 µL	-
	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-

#### Sensitization

There is no data available.

#### Carcinogenicity

##### Classification

Product/ingredient name	OSHA	IARC	NTP	ACGIH	EPA	NIOSH
Xylene	-	3	-	A4	-	-
m-Xylene	-	3	-	A4	-	-
Titanium dioxide	-	2B	-	A4	-	+
p-Xylene	-	3	-	A4	-	-
Ethylbenzene	-	2B	-	A3	-	None.
o-Xylene	-	3	-	A4	-	-
Carbon black	-	2B	-	A3	-	+
Silicon dioxide	-	3	-	-	-	-

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 3	Not applicable.	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

## Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
Toluene	Category 2	Not determined	Not determined

### Aspiration hazard

Name	Result
Toluene	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Dermal contact. Eye contact. Inhalation. Ingestion.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : No known significant effects or critical hazards.  
**Potential delayed effects** : No known significant effects or critical hazards.

#### Long term exposure

**Potential immediate effects** : No known significant effects or critical hazards.  
**Potential delayed effects** : No known significant effects or critical hazards.

#### Potential chronic health effects

**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

There is no data available.



## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
Xylene	Acute IC50 10 mg/L	Algae	72 hours
	Acute LC50 8500 µg/L Marine water	Crustaceans - Palaemonetes pugio	48 hours
m-Xylene	Acute LC50 13400 µg/L Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 4900 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
Titanium dioxide	Acute EC50 7090 µg/L Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 5000 µg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 8400 µg/L Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 5.83 mg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute LC50 3 mg/L Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 5.5 ppm Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
p-Xylene	Acute LC50 1000 mg/L Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 0.984 mg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute EC50 3200 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
Ethylbenzene	Acute EC50 5030 µg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2 µl/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute EC50 4600 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
o-Xylene	Acute EC50 3600 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 2970 µg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 5200 µg/L Marine water	Crustaceans - Americamysis bahia	48 hours
	Acute LC50 4200 µg/L Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 1000 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 4700 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
Toluene	Acute EC50 1390 µg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 38000 µg/L Marine water	Crustaceans - Cancer magister - Zoea	48 hours
	Acute LC50 7600 µg/L Fresh water	Fish - Oncorhynchus mykiss	96 hours
Toluene	Acute EC50 433 ppm Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 12500 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/L Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/L Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/L Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 500000 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Chronic NOEC 1000 µg/L Fresh water	Daphnia - Daphnia magna	21 days

### Persistence and degradability

There is no data available.

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Xylene	3.12	8.1 to 25.9	low
m-Xylene	3.2	8.1 to 25.9	low
Titanium dioxide	-	352	low
p-Xylene	3.15	8.1 to 25.9	low
Ethylbenzene	3.6	-	low
o-Xylene	3.12	8.1 to 25.9	low
Toluene	2.73	90	low

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.







## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Dispose material in accordance with all local, state, and federal regulations.

**United States - RCRA Toxic hazardous waste "U" List**

Ingredient	CAS #	Status	Reference number
Xylene	1330-20-7	Listed	U239
p-Xylene	106-42-3	Listed	U239
m-Xylene	108-38-3	Listed	U239
o-Xylene	95-47-6	Listed	U239

## Section 14. Transport information

	DOT Classification	IMDG	IATA
<b>UN number</b>	UN1210	UN1210	UN1210
<b>UN proper shipping name</b>	PRINTING INK	PRINTING INK. Marine pollutant (m-Xylene, p-Xylene)	PRINTING INK
<b>Transport hazard class(es)</b>	3 	3  	3 
<b>Packing group</b>	III	III	III
<b>Environmental hazards</b>	No.	Yes.	No.
<b>Additional information</b>	- Limited Quantity Exemption	- Limited Quantity Exemption	- Limited Quantity Exemption

**AERG** : 129

**DOT-RQ Details** : Xylene 100 lbs / 45.4 kg [13.946 gal / 52.791 L]  
p-Xylene 100 lbs / 45.4 kg [13.946 gal / 52.791 L]

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** : **TSCA 8(a) PAIR:** p-Xylene  
**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined  
**United States inventory (TSCA 8b):** All components are listed or exempted.  
**Clean Water Act (CWA) 307:** Ethylbenzene; Toluene  
**Clean Water Act (CWA) 311:** Xylene; p-Xylene; m-Xylene; Ethylbenzene; o-Xylene; Toluene



## Section 15. Regulatory information

**Clean Air Act Section 112** : Listed

**(b) Hazardous Air Pollutants (HAPs)**

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : Not applicable.

#### Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Xylene	30 - 60	Yes.	No.	No.	Yes.	No.
m-Xylene	30 - 60	Yes.	No.	No.	Yes.	No.
Titanium dioxide	10 - 30	No.	No.	No.	No.	Yes.
p-Xylene	10 - 30	Yes.	No.	No.	Yes.	No.
Ethylbenzene	5 - 10	Yes.	No.	No.	Yes.	Yes.
o-Xylene	5 - 10	Yes.	No.	No.	Yes.	No.
Carbon black	5 - 10	No.	No.	No.	No.	Yes.
Toluene	0.1 - 1	Yes.	No.	No.	Yes.	Yes.

### SARA 313

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	Xylene	1330-20-7	30 - 60
	m-Xylene	108-38-3	30 - 60
	p-Xylene	106-42-3	10 - 30
	Ethylbenzene	100-41-4	5 - 10
	o-Xylene	95-47-6	5 - 10
	Manganese, 4-[(4-Chloro-5-Methyl-2-Sulfophenyl)Azo]-3-Hydroxy-2-Naphthalenecarboxylic Acid Complex	12238-31-2	1 - 5
<b>Supplier notification</b>	Xylene	1330-20-7	30 - 60
	m-Xylene	108-38-3	30 - 60
	p-Xylene	106-42-3	10 - 30
	Ethylbenzene	100-41-4	5 - 10
	o-Xylene	95-47-6	5 - 10
	Manganese, 4-[(4-Chloro-5-Methyl-2-Sulfophenyl)Azo]-3-Hydroxy-2-Naphthalenecarboxylic Acid Complex	12238-31-2	1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

#### **Massachusetts**

: The following components are listed: Xylene; Titanium dioxide; p-Xylene; m-Xylene; Ethylbenzene; o-Xylene; Carbon black; Silicon dioxide

## Section 15. Regulatory information

- New York** : The following components are listed: Xylene; p-Xylene; m-Xylene; Ethylbenzene; o-Xylene
- New Jersey** : The following components are listed: Xylene; Titanium dioxide; p-Xylene; m-Xylene; Ethylbenzene; o-Xylene; Carbon black
- Pennsylvania** : The following components are listed: Xylene; Titanium dioxide; p-Xylene; m-Xylene; Ethylbenzene; o-Xylene; Carbon black; Manganese, 4-[(4-Chloro-5-Methyl-2-Sulfophenyl)Azo]-3-Hydroxy-2-Naphthalenecarboxylic Acid Complex; Silicon dioxide

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

**WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	Yes.	No.	No.	No.
Ethylbenzene	Yes.	No.	41 µg/day (ingestion) 54 µg/day (inhalation)	No.
Carbon black	Yes.	No.	No.	No.
Toluene	No.	Yes.	No.	7000 µg/day (ingestion) 13000 µg/day (inhalation)

## Section 16. Other information

### History

- Date of issue mm/dd/yyyy** : 07/15/2015
- Version** : 1
- Prepared by** : KMK Regulatory Services Inc.
- Key to abbreviations** : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

