

Project: \_\_\_\_\_

Architect: \_\_\_\_\_

Contractor: \_\_\_\_\_

Suppliers: \_\_\_\_\_

Dealer: \_\_\_\_\_

Engineer: \_\_\_\_\_

Location: \_\_\_\_\_

Date: \_\_\_\_\_

## SPECIFICATIONS

<b>Capacity<sup>(1)</sup></b>	11.5–34.6 gpd
<b>Voltage</b>	120, 208 or 240VAC
<b>Amps</b>	11.5 or 16 Amps
<b>Weight: Unit only   Operating</b>	27 lbs.
<b>Warranty</b>	5 Years on all parts

<sup>(1)</sup>Rated capacity and energy factor test done and current draw measured in accordance with AHAM DH-1 2008 at 80°F/60% RH inlet air at 0.0 ESP.

## FEATURES

<b>High capacity</b>	One unit can provide between 92 and 277 pints per day or 11.5 and 34.6 gallons per day.
<b>Electrode type humidifier</b>	Generates steam by energizing two electrodes that extend into the steam canister. Current flowing in between the electrodes causes the water to boil creating steam.
<b>Water requirements</b>	Use standard potable water or softened water. Reverse Osmosis "RO" or deionized water is not recommended. Water conductivity 75-1250 EC.
<b>Easy to install</b>	Fan Pack mounts to top of steam humidifier. Can also be remotely mounted with steam hose part number 5940 (sold separately).
<b>Accessories included AS35FP</b>	Fan pack, Vapor-logic® control, RH Transmitter, 7" steam hose and 2' of drain tubing.
<b>Display panel</b>	Includes on/off switch. Display panel to show fill, drain, steam, operations and diagnostics.
<b>Internal control board</b>	Manages the complete operation of the humidifier. Fills and drains to maintain proper amperage draw, water level and notifies when service is required.
<b>Back flow protection</b>	Air gap in the fill cap prevents pressure buildup.
<b>Water level sensor</b>	Prevents the steam cylinder from overflowing
<b>Automatic drain and fill cycle</b>	Unit flushes and fills periodically to maintain the proper conductivity.
<b>Optional drain tempering</b>	Unit uses cold inlet water to temper the cylinder water reducing the drain water temperature below 140°F to protect PVC piping and condensation pumps.
<b>End-of-season drain</b>	After a 72-hour period with no call for humidity, the humidifier will drain the water from the canister. Unit will remain in stand-by mode until next call for humidification.
<b>Operating time monitor</b>	Accumulates actual humidifier run time to activate periodic drain and fill cycles, end-of-season drain function and monitors the life of canister.
<b>Easy to maintain</b>	No cleaning or scrubbing, simply remove the steam canister and replace.



## PRINCIPLE OF OPERATION

The Anden AS35FP Steam Humidifier operates utilizing electrode technology: current flowing between two electrodes in the disposable steam canister boils water to generate steam. Drain and fill valves in the humidifier work together to maintain the correct water level in the canister to satisfy the demand for humidity based on the electrical conductivity of the water.

## APPLICATION

The Anden Model AS35FP disperses steam directly into the area to be humidified through a dedicated fan pack that is powered by the humidifier itself.

STEAM CAPACITY		VOLTAGE	CURRENT DRAW	
Pints/Day	Gallon/Day		Amps	kW
92	11.5	120V	11.5	1.4
128	16.0		16.0	1.9
164	20.5		11.5v	2.4
240	30.0	208V	16.0	3.3
186.4	23.3		11.5	2.8
276.8	34.6		16.0	3.8



The submittal is intended to show general, overall product dimensions and provide guidance for installation clearance. Drawings are not to scale.