



## Camshelving® Elements Series

### Mobile – Post Kits

**2 Post Heights (with Casters)**  
70" (1778 mm), 78" (1980 mm)

**3 Shelf Widths**  
18" (460 mm), 21" (540 mm),  
24" (610 mm)



• **Post Kit includes:**

2 Mobile Posts without leveling feet installed, 1 Top Post Connector, 1 Bottom Post Connector, 8 Post Connector Wedges in a bag and instructions. Casters are not included and must be ordered separately.

### Features & Benefits

#### Strong Technology

Posts are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up to 60" (1530 mm) long hold up to 900 lbs. per unit of evenly distributed static weight.

#### Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

#### Shelving for Life

Non-corrosive design will endure all areas of operation, dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

#### Requires minimal assembly

Can be put together with the use of a rubber mallet.

#### Premium Casters

Stainless steel with a non-marking polyurethane wheel. Recommended for use in wet areas or in walk-in refrigerators and freezers.

#### Standard Casters

Zinc plated with a non-marking polyurethane wheel. Recommended for use in dry storage areas.

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



**Mobile Four Shelf Unit with Vented Shelf Plates.**  
(Built using 2 Mobile Post Kits and 4 Mobile Shelf Kits.)



**Post Kit includes two Posts, one set of Post Connectors, and a bag of 8 Post Connector Wedges. Casters not included.**

### Approvals



Components



© Cambio Manufacturing Company 5801 Skylab Road, Huntington Beach, CA 92647-2056, U.S.A.  
Telephone 714 848 1555 Toll Free 800 854 7631

Customer Service Department 800 833 3003

# Camshelving® Elements Series

## Mobile – Post Kits

**2 Post Heights (with Casters)**  
70" (1778 mm), 78" (1980 mm)

**3 Shelf Widths**  
18" (460 mm), 21" (540 mm),  
24" (610 mm)



• **Post Kit includes:**

2 Mobile Posts without leveling feet installed, 1 Top Post Connector, 1 Bottom Post Connector, 8 Post Connector Wedges in a bag and instructions. Casters are not included and must be ordered separately.

### Stationary – Post Kits

CODE	WIDTH IN. (MM)	HEIGHT IN. (MM)	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
EMPK1870	18" 460 mm	70" 1778 mm	8.66 (0.46)	3,93 (0,01)
EMPK2170	21" 540 mm	70" 1778 mm	8.84 (0.46)	4,01 (0,01)
EMPK2470	24" 610 mm	70" 1778 mm	9.02 (0.46)	4,09 (0,01)
EMPK1878	18" 460 mm	78" 1980 mm	9.50 (0.52)	4,31 (0,01)
EMPK2178	21" 540 mm	78" 1980 mm	9.68 (0.52)	4,39 (0,01)
EMPK2478	24" 610 mm	78" 1980 mm	9.86 (0.52)	4,47 (0,01)

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_

### Casters and Donut Bumper

CODE	DESCRIPTION	DIAMETER IN. (MM)	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
<b>Premium Casters</b>				
EMSCBP	Swivel with Brake	5" 127 mm	4.75 (0.16)	2,16 (0,005)
EMSCP	Swivel No Brake	5" 127 mm	4.35 (0.16)	1,97 (0,005)
<b>Standard Casters</b>				
EMSCB	Swivel with Brake	5" 127 mm	4.75 (0.16)	2,16 (0,005)
EMSC	Swivel No Brake	5" 127 mm	4.35 (0.16)	1,97 (0,005)
<b>High Density Caster</b>				
EHDC	High Density No Brake		2.01 (0.048)	0,91 (0,001)
<b>Bumper</b>				
CSHDDDB	Donut Bumper	5" 127 mm	2.01 (0.05)	0,34 (0,001)

Casters Case Pack: 2

Bumper Case Pack: 4

**PREMIUM CASTERS** – Stainless steel with a non-marking polyurethane wheel. Recommended for use in wet areas or in walk-in refrigerators and freezers.

**STANDARD CASTERS** – Zinc plated with a non-marking polyurethane wheel. Recommended for use in dry storage areas.

### Architect Specs

**Posts:** Proprietary non-corrosive composite material.  
**Post Connectors:** Glass Filled Polypropylene.  
**Mobile Traverses:** Proprietary non-corrosive composite material.  
**Vented/Solid Shelf Plates:** Reinforced polypropylene with Camguard® antimicrobial.  
**Divider Bars:** Glass Filled Nylon.  
**Mobile Dovetails:** Resin Nylon  
**Wedges:** Resin Polypropylene

### Standard Color

☐ Brushed Graphite (580)

### Approvals



**Components**

**CAMBRO**  
TRUSTED FOR GENERATIONS™

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, CA 92647-2056, U.S.A.  
 Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003