

Proudly Made in the USA

Tulsa Rig Iron TT-560



TT-560 Triplex Pump

Designed For Demanding Pumping Applications

- 6" Stroke
- 500 GPM Continuous Duty Rated

Recommended Uses

- Pressure Testing
- Chemical Water Injection
- All Drilling Applications
- Industrial Applications
- Well Servicing

TT-560- 6" Stroke - 500 hp - Continuous Duty

Strokes per Minute			400	300	200	100	50
Piston Size	Area Sq. Inches	Output Gal/Rev	Output Gallons per Minute/Pressure PSI				
5"	19.6349	1.530	612	459	306	153	77
			1400	1875	2545	2545	2545
4.5"	15.9043	1.239	496	372	248	124	62
			1725	2300	3140	3140	3140
4"	12.5663	0.979	392	294	196	98	49
			2200	2925	3980	3980	3980
3.5"	9.6211	0.750	300	225	150	75	38
			2850	3815	5000	5000	5000
3"	7.0685	0.551	220	165	110	55	28
			3890	5000	5000	5000	5000

- Based on 100% volumetric efficiency and 90% mechanical efficiency
- Standard 5,000 psi fluid end
- For intermittent applications at higher pressure contact Tulsa Rig Iron

Options and Usage**Options:**

- Bare Pump Only
- Pump with Chainbox
- Complete Skidded Pump Package

Used Often For:

- Horizontal Directional Drilling
- Reverse Circulation
- Hydrostatic Testing
- Water Blast
- Workover Applications

Utilizing roller bearings throughout, our pumps are built to last! They are designed to be easily maintained and are capable of being completely rebuilt.

Our TT-560 features a smaller footprint and lighter weight than competing models, making it completely legal load size and weight in most instances.