Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : AIRX 79+ Hospital Disinfectant & Odor Counteractant

EPA ID Number: 10807-177-44089

Material number : 1014598 / A00221

Manufacturer or supplier's details

Company : The Bullen Companies

Airex Laboratories

Address : 1640 Delmar Drive

Folcroft, PA 19032

Telephone : 610-534-8900

**Emergency telephone numbers** 

For SDS Information : CHEMTEL: 800-255-3924

For a Medical Emergency

For a Transportation : CHEMTEL: 800-255-3924

Emergency

### **SECTION 2. HAZARDS IDENTIFICATION**

### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas	
Colour	white, light yellow	
Odour	characteristic	

## **GHS Classification**

Flammable aerosols : Category 2
Gases under pressure : Liquefied gas
Eye irritation : Category 2A

**GHS Label element** 

Hazard pictograms :





Signal word : Warning

Hazard statements : H223 Flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

Precautionary statements : **Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

use.

P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention. Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **Potential Health Effects**

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### **Hazardous components**

Chemical Name	CAS-No.	Concentration [%]
ethanol	64-17-5	>= 50 - < 70
butane	106-97-8	>= 10 - < 20
propane	74-98-6	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

advice.

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

Wash contaminated clothing before re-use.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

:

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Always replace cap after use.

Do not breathe vapours or spray mist.

Conditions for safe storage

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	TWA	1,000 ppm	ACGIH

Version 1.0	Revision Date 05/30/2015	Print Date 06/11/2015

		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
•		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0

# **Biological occupational exposure limits**

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
PROPAN-2-OL	67-63-0	Acetone	Urine	End of	40 mg/l	ACGIH BEI
				shift at	_	
				end of		
				workwee		
				k		

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location.
Tightly fitting safety goggles

Skin and body protection : impervious clothing

Choose body protection according to the amount and

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : white, light yellow
Odour : characteristic
Odour Threshold : no data available

pH : 10.3 - 10.8

Melting point/freezing point : no data available Boiling point : no data available

Flash point :

no data available

Evaporation rate : no data available Flammability (solid, gas) : Flammable aerosol.

Upper explosion limit : no data available
Lower explosion limit : no data available
Vapour pressure : no data available
Relative vapour density : no data available
Density : 0.840 g/cm3

Solubility(ies)

Water solubility : completely soluble Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: no data available

Auto-ignition temperature : not determined

Thermal decomposition : no data available

Viscosity

Viscosity, kinematic : no data available

Heat of combustion : 29.16 kJ/g

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Reducing agents Ammonium salts

Hazardous decomposition

products

: Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

# **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

**Components:** 

ethanol:

Acute oral toxicity : LD50 Oral rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 rat: 124.7 mg/l

Exposure time: 4 h

butane:

Acute inhalation toxicity : LC50 mouse: 1,237 mg/l

Exposure time: 2 h

LC50 rat: 1,355 mg/l

propane:

Acute inhalation toxicity : LC50 mouse: 1,237 mg/l

Exposure time: 2 h

LC50 rat: 658 mg/l Exposure time: 4 h

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

LC50 rat: 1,355 mg/l

propan-2-ol:

Acute oral toxicity : LD50 Oral rat: 4,396 mg/kg

Method: Calculation method

#### Skin corrosion/irritation

**Product:** 

Remarks: May cause skin irritation in susceptible persons.

## Serious eye damage/eye irritation

**Product:** 

Remarks: Severe eye irritation

Remarks: May cause irreversible eye damage.

### Respiratory or skin sensitisation

no data available

### Germ cell mutagenicity

no data available

## Carcinogenicity

no data available

## Reproductive toxicity

no data available

ethanol:

butane:

propane:

propan-2-ol:

## STOT - single exposure

no data available

### STOT - repeated exposure

no data available

### **Aspiration toxicity**

no data available

#### **Further information**

## **Product:**

Remarks: no data available

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

no data available

## Persistence and degradability

no data available

## **Bioaccumulative potential**

**Product:** 

Partition coefficient: n-

octanol/water <u>Components:</u> butane :

Partition coefficient: n-

octanol/water

: Pow: 2.89

Mobility in soil

no data available

### Other adverse effects

no data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

: Remarks: no data available

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: no data available

## **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

#### **SECTION 15. REGULATORY INFORMATION**

This product is regulated under the United States Federal Insecticide, Fungicide and Rodenticide Act (FIFRA).

## Pesticide Labeling Information Required Under U.S. FIFRA Regulations

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
sodium nitrite	7632-00-0	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ammonia, anhydrous	7664-41-7	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Sudden Release of Pressure Hazard

Acute Health Hazard

Fire Hazard

SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

biphenyl-2-ol 90-43-7

## The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

**DSL** This product contains one or several components that are not on the

Canadian DSL nor NDSL.

AICS
Not in compliance with the inventory
NZIOC
Not in compliance with the inventory
PICCS
Not in compliance with the inventory
IECSC
Not in compliance with the inventory


### **Inventory Acronym and Validity Area Legend:**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

## **SECTION 16. OTHER INFORMATION**

## **Further information**

## NFPA:



Special hazard.

# HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	2

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### OSHA GHS Label Information:

Hazard pictograms







Signal word : Warning:

Hazard statements : Flammable aerosol. Contains gas under pressure; may explode if heated. Causes

serious eye irritation.

Precautionary statements

Version 1.0 Revision Date 05/30/2015 Print Date 06/11/2015

> Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear eye protection/ face protection.

> Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.0
Revision Date:	05/30/2015
Print Date:	06/11/2015

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

1014598