



# EASY TASK™



## Thermoplastic Spray Buff

*This spray buffing compound combines detergents, thermoplastics and solvent for the answer to terrific looking floors. Simply spray on floors and polish with spray buff pad to easily remove black heel marks, scuffs, scratches and dullness. Leaves a "wet look" gloss. Exclusive self-emulsifying system will not allow any build-up on floors. Regular use of this spray buff will allow the user to reduce stripping and rewaxing procedures by over 75%. Spray buff leaves floor finish very hard and durable, yet very slip resistant. Stops powdering. May be used over most floor finishes successfully.*



### Uses

- For all finishes
- For all floors
- Use with any speed floor machine

### Features

- Effective repair of all floor finish types. Use appropriate pad/brush for the prescribed maintenance task.
- Versatile - The perfect product for use with conventional and high speed equipment. Provides excellent lubricity to pad surface for a higher shine.
- Easy-to-use - Just lightly mist ahead of floor machine path, buff to a high shine.

### Properties

Buffability .....	Excellent
Color (dry) .....	Clear
Color (liquid) .....	Milky green
Fragrance .....	Clean bouquet
Freeze/thaw stability .....	Keep from freezing
Gloss .....	Excellent
Heel mark resistance .....	Excellent
pH .....	8.0 - 9.5
Recoat .....	Excellent
Specific gravity .....	1.0
Shelf life .....	1 year

### Directions For Use

**Read the entire label before using this product.**

1. Remove gross soil and dust mop the floor.
2. Spray a light mist of product on the floor in front of the floor machine. DO NOT OVERWET.
3. Using a nylon or polyester spray buff pad, buff the floor where the fine mist of spray buff has been applied.
4. Flip or change pad as necessary.
5. After spray buffing the floor is completed, dust mop the floor if dust is still present.

**PLEASE NOTE: In order for spray buff to work correctly, three or four base coats of floor finish must be applied before using spray buff in order to achieve maximum gloss and wear properties.** Heavy traffic areas may require dust mopping, followed by damp mopping, followed by spray buffing. Use of this spray buff will eliminate powdering and will never yellow the floor. *Slip resistance meets or exceeds (ASTM D 2047-04) James Machine 0.5 minimum.*

### Safety

Keep out of reach of children. For institutional and commercial use. **CAUTION: MAY CAUSE EYE IRRITATION.** Contains ethylene glycol. Harmful if swallowed. Use with adequate ventilation. Do not breathe vapor or mist. Avoid contact with eyes, skin, and clothing. **FIRST AID:** If Inhaled: Remove to fresh air. If splashed on skin or in eyes, flush with large quantities of water. Seek medical attention if irritation persists. If swallowed, call a physician immediately.

### Available In

Case/12 - Quarts (946 mL): Item #60812-00  
Case/4 - 1 Gallon (3.78 L): Item #60804-00

