

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory-Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

SPRAY KLEEN - MULTI-SURFACE
NEUTRAL CLEANER

Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.

Section I

NA = Not Applicable NIA = No Information Available

Manufacturer's Name

Sunburst Chemicals, Inc.

Emergency Telephone Number

1-866-303-6943 (7 days/24 hours)

Address (Number, Street, City, State, and ZIP Code)

220 W. 86th St.

Telephone Number For Information

(952) 884-3144

Bloomington, MN 55420

Date Prepared

10-20-10

Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
---	----------	-----------	-----------------------------	-------------

Contains no hazardous ingredients.

Section III - Physical/Chemical Characteristics

Boiling Point	212°F.	Specific Gravity (H ₂ O= 1)	1.01
Vapor Pressure (mm Hg.)	NIA	Melting Point	NA
Vapor Density (AIR= 1)	NIA	Evaporation Rate (Butyl Acetate = 1)	NIA

Solubility In Water

Complete.

Appearance and Odor

Red liquid, slight odor.

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) None.	Flammable Limits	LEL NA	UEL NA
Extinguishing Media Water, CO ₂ , Dry chemical.			
Special Fire Fighting Procedures None.			
Unusual Fire and Explosion Hazards None.			

HMIS	NFPA			
1 HEALTH	HEALTH HAZARD	FIRE HAZARD	SPECIFIC HAZARD	REACTIVITY
2 FLAMMABILITY	4 Deadly	Flash Points	Oxidizer OX	4 May detonate
0 REACTIVITY	3 Extreme danger	4 Below 73° F (Boiling pt. below 100° F)	Acid ACID	3 Shock and heat may detonate
A PERSONAL	2 Hazardous	3 Below 73° F (Boiling pt. at/above 100° F)	Alkali ALK	2 Violent chemical change
PROTECTION	X 1 Slightly hazardous	and/or at/above 73° F - not exceeding 100° F	Corrosive COR	1 Unstable if heated
	0 Normal material	X 2 Above 100° F, Not Exceeding 200° F	Use NO WATER	X 0 Stable
		1 Above 200° F	Radioactive	
		0 Will not burn		

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	
Incompatibility (<i>Materials to Avoid</i>) None.			
Hazardous Decomposition or Byproducts None.			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Routes(s) of Entry:	Inhalation?	Skin?	Ingestion?
	NO	NO	NO
Health Hazards (<i>Acute and Chronic</i>) <u>ACUTE</u> - irritation to eyes and skin, distress to digestive tract, diarrhea. <u>CHRONIC</u> - NIA, but ethylene glycol monobutyl ether is suspected carcinogen.			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO
Signs and Symptoms of Exposure <u>EXTERNAL</u> - redness of skin or eyes. <u>INTERNAL</u> - foul taste.			
Medical Conditions Generally Aggravated by Exposure Open sores or wounds.			
Emergency and First Aid Procedures <u>EXTERNAL</u> - thoroughly rinse with water for at least 15 minutes. Get medical attention if irritation persists. <u>INTERNAL</u> - drink a large quantity of milk or water. Get immediate medical attention.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Absorb spilled material with an absorbent material such as clay, sawdust, or sand. Sweep up as much of this as possible and place in a sealed, labeled container or in a proper landfill. Thoroughly rinse the affected area with water.	
Waste Disposal Method Spilled material should be collected as above for disposal in a landfill according to Federal, State and Local regulations. Any rinsing of the affected area should also be in accordance with Federal, State and Local regulations.	
Precautions to Be Taking in Handling and Storing Keep tightly closed when not in use.	
Other Precautions Avoid contact of product (or its use solutions) with skin, eyes or clothing. Keep out of reach of children.	

Section VIII – Control Measures

Respiratory Protection (<i>Specify Type</i>) Not required.		
Ventilation	Local Exhaust NIA	Special NIA
	Mechanical (<i>General</i>) NIA	Other NIA
Protective Gloves Rubber or vinyl.		Eye Protection Safety glasses, goggles recommended.
Other Protective Clothing or Equipment Not required.		
Work/Hygienic Practices Always wash hands after handling.		