



L.O.E. Stripper

low odor emulsifier

With low VOCs and a non-butyl formula, this low odor emulsifier is an aggressive solution. L.O.E. is recommended for health care and other areas where sensitivity to scent is high and/or the typical strong stripper odor presents a problem. L.O.E. is highly dilutable to provide flexibility to meet floor conditions.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, OH 43537
1-800-537-8990
www.spartanchemical.com

LOW ODOR AND LOW VOCs:

L.O.E. Stripper is fragrance free and free of chemical substances that cause unpleasant odors. Low VOC's (volatile organic compounds). L.O.E. Stripper will not negatively affect indoor air quality. Excellent for use in health care facilities and confined areas. Use L.O.E. Stripper anywhere and anytime ... 24 hours a day!

NO BUTYL:

Contains no butoxyethanol ... an important feature where the use of butyl is restricted and for those who prefer a non-butyl Stripper.

HIGH PERFORMANCE - EASY RINSE:

L.O.E. Stripper's high performance solvent base speeds the emulsification process of cross-linked acrylic finish. L.O.E. Stripper works fast and efficiently. Even heavy build ups require little effort for removal. L.O.E. Stripper rinses easily and no flood rinsing is required. A real time and labor saver.

CONCENTRATE FORMULATED FOR HIGH DILUTION AND MAXIMUM ECONOMY:

L.O.E. Stripper is a true concentrate and as a consequence, economical in use. Dilute L.O.E. Stripper up to 1:20 (6 oz./gal. of water) and remove even tough finish build-ups.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

1. Depending on build-up, dilute L.O.E. Stripper from 1:1 to 1:20 (6 oz. to 128 oz./gal. of water) with warm water. When minimal fragrance is desired, dilute L.O.E. Stripper with room temperature water. Automatic scrubbers: dilute up to 1:10 (12 oz./gal. of water).
2. Liberally apply L.O.E. Stripper with mop to small section (100 sq. ft.) of floor. Be sure to completely cover floor to baseboards.
3. After 3 to 5 minutes, agitate the wetted section with mop or machine scrub. Pick up solution using mop, wet vac or automatic scrubber.
4. Detail damp mop with clear water to remove residue or squeegee tracks as necessary. Flood rinsing is not required before recoating.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.



SPECIFICATIONS:

Total Active Ingredients - 39.7%
Specific Gravity - 1.018 @ 24°C/75°F
pH Concentrate - 13.0-13.7
Flash Point (Cleveland Open Cup) - None
Stability:
a. Shelf @ 24°C/75°F - In excess of one year
b. Accelerated @ 49°C/120°F - In excess of 90 days
c. Freeze/Thaw Cycle - Freezes and thaws with complete clarity
Rinsability - rinses completely in hot or cold water.
Biodegradable
Phosphate free



ISSA MEMBER
The Experts
on Cleaning and Maintenance

Distributed by:

PACKAGING	
006160	275-gallon totes
006155	55-gallon drum
006130	30-gallon drum
006115	15-gallon drum
006105	5-gallon pail
006104	1-gallon (4 per case)



Label copy is provided in English, Spanish and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product available worldwide. For institutional and industrial use only.

© SCC 5/11 L0061