

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
Product name : Solutions Plus Laser Plus Stripper
Product code : 155-9244

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Floor strip products

1.3. Supplier

American Cleaning Solutions
39-30 Review Avenue
Long Island City, NY 11101
T (718) 392-8080

1.4. Emergency telephone number

Emergency number : INFOTRAC: 800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (dermal)	H312	Harmful in contact with skin
Category 4		
Skin corrosion/irritation	H314	Causes severe skin burns and eye damage
Category 1A		

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H312 - Harmful in contact with skin
H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P260 - Do not breathe dust/mist/spray
P264 - Wash hands and forearms thoroughly after handling
P280 - Wear protective gloves/eye protection/face protection
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P302+P352 - If on skin: Wash with plenty of soap and water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center/doctor
P312 - Call a poison center/doctor... if you feel unwell
P321 - Specific treatment (see First aid measures on this label)
P362+P364 - Take off contaminated clothing and wash it before reuse
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations

2.3. Other hazards which do not result in classification

No additional information available

Solutions Plus Laser Plus Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
butyl glycoether	(CAS No) 111-76-2	30 - 50	Flam. Liq. 4, H227 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:gas), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
2-aminoethanol	(CAS No) 141-43-5	10 - 20	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314
Potassium Hydroxide, 45%=<conc<50%, aqueous solutions	(CAS No) 1310-58-3	5 - 10	Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Immediately call a poison center or doctor/physician. Specific measures (see supplier information on this label). Wash with plenty of soap and water. Wash contaminated clothing before reuse. Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/injuries	: Causes severe skin burns and eye damage.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Thermal decomposition generates : corrosive vapors.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

Solutions Plus Laser Plus Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames}. - No smoking.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Do not breathe dust/mist/spray. Avoid contact during pregnancy/while nursing.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Keep container closed when not in use. Keep in fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butyl glycolether (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
2-aminoethanol (141-43-5)		
ACGIH	ACGIH TWA (ppm)	3 ppm (Ethanolamine; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	6 ppm (Ethanolamine; USA; Short time value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Eye & skin irr
OSHA	OSHA PEL (TWA) (mg/m ³)	6 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	3 ppm

Solutions Plus Laser Plus Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)		
ACGIH	Remark (ACGIH)	URT, eye, & skin irr

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves/eye protection/face protection protective gloves

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: clear
Odor	: Butyl
Odor threshold	: No data available
pH	: 12.5
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212 - 220 °F
Flash point	: 200 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Combustible liquid.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: Same as water
Relative density	: 1
Solubility	: Soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

Solutions Plus Laser Plus Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. May release flammable gases. Thermal decomposition generates : corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Dermal: Harmful in contact with skin.

Solutions Plus Laser Plus Stripper	
ATE US (dermal)	1072.061 mg/kg body weight
butyl glycolether (111-76-2)	
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450 - 486 ppm/4h 450-486,Rat
ATE US (dermal)	435.000 mg/kg body weight
ATE US (gases)	450.000 ppmV/4h
ATE US (vapors)	2.170 mg/l/4h
ATE US (dust, mist)	2.170 mg/l/4h
2-aminoethanol (141-43-5)	
LD50 oral rat	1720 mg/kg (Rat)
LD50 dermal rabbit	1018 mg/kg (Rabbit)
ATE US (oral)	1720.000 mg/kg body weight
ATE US (dermal)	1018.000 mg/kg body weight
Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
LD50 oral rat	273 mg/kg (Rat)
ATE US (oral)	273.000 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.
pH: 12.5

Serious eye damage/irritation : Not classified
pH: 12.5

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

butyl glycolether (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Solutions Plus Laser Plus Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed. Harmful in contact with skin.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

2-aminoethanol (141-43-5)	
LC50 fish 1	150 mg/l (LC50; 96 h; Salmo gairdneri)
EC50 Daphnia 1	140 mg/l (EC50; 24 h)
Threshold limit algae 2	35 mg/l (EC50; 72 h)
Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
LC50 fish 2	80 mg/l (LC50; 96 h)

12.2. Persistence and degradability

Solutions Plus Laser Plus Stripper	
Persistence and degradability	Not established.
butyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31
2-aminoethanol (141-43-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	0.8 g O ₂ /g substance
Chemical oxygen demand (COD)	1.34 g O ₂ /g substance
ThOD	2.49 g O ₂ /g substance
BOD (% of ThOD)	0.32
Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the components available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

Solutions Plus Laser Plus Stripper	
Bioaccumulative potential	Not established.
butyl glycolether (111-76-2)	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
2-aminoethanol (141-43-5)	
Log Pow	-1.91
Bioaccumulative potential	Bioaccumulation: not applicable.
Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Solutions Plus Laser Plus Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)
2-aminoethanol (141-43-5)	
Surface tension	0.05 N/m

12.5. Other adverse effects

Effect on the global warming	: No known effects from this product.
GWPmix comment	: No known effects from this product.
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: NA1760 Compounds, cleaning liquid (Contains Potassium Hydroxide), 8, II
UN-No.(DOT)	: NA1760
Proper Shipping Name (DOT)	: Compounds, cleaning liquid Contains Potassium Hydroxide
Class (DOT)	: 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Symbols	: D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN requiring a technical name

Solutions Plus Laser Plus Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. N37 - This material may be shipped in an integrally-lined fiber drum (1G) which meets the general packaging requirements of subpart B of part 173 of this subchapter, the requirements of part 178 of this subchapter at the packing group assigned for the material and to any other special provisions of column 7 of the 172.101 table. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.

TDG

Transport by sea

Air transport

SECTION 15: Regulatory information

15.1. US Federal regulations

butyl glycolether (111-76-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2-aminoethanol (141-43-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	1000 lb

15.2. International regulations

CANADA

No additional information available

Solutions Plus Laser Plus Stripper

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Revision date : 04/15/2015

Other information : None.

Full text of H-phrases:

H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Personal protection : B

B - Safety glasses, Gloves

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product