



Super Spraybuff

solvent-based spraybuffing concentrate

Super Spraybuff is a solvent-based detergent and polymer emulsion. It deep cleans, repairs and restores the shine of high gloss finishes. It will not yellow and is powder resistant.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee, OH 43537
 1-800-537-8990
 www.spartanchemical.com

CLEANS AND SHINES IN ONE OPERATION:

Super Spraybuff's unique chemical system incorporates a detergent and two solvents (water based and aliphatic) providing rapid penetration and removal of embedded soil, black heel marks, scuffs, and surface scratches. The product's third primary ingredient, acrylic urethane polymer, enhances the original high gloss and beauty of the base finish coat, restoring it to its optimum appearance.

REDUCES FLOOR MAINTENANCE COSTS:

Consistent use of Super Spraybuff substantially reduces overall floor maintenance costs by eliminating the need for time consuming deep stripping, resealing, and refinishing.

PREVENTIVE MAINTENANCE:

Super Spraybuff, used on a regular basis, is an excellent preventive maintenance product. The activity of the acrylic urethane polymer hardens the original finish surface, making it more resistant to black marks, scuffs, and scratches.

PLEASANT AND SAFE TO USE:

Unlike many solvent based spray buffing compounds, Super Spraybuff does not produce unpleasant fumes or lingering solvent odors.

STABLE:

Super Spraybuff is stable in its concentrated form and will not separate. For routine repair and economy, Super Spraybuff may be diluted 1:1 with cool water.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before use, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

- Spraybuffing, or it could be called spray cleaning, consists of spraying a small area of floor with one of Spartan's spray buffing products. Immediately clean and polish the area until it is cleaned and shined with a floor machine equipped with a buffing pad and pad holder.
- A floor must have a minimum of three coats of a floor wax or finish prior to spraybuffing.
- After sweeping and dusting, floors should be scrubbed or damp mopped before spraybuffing.
- Too much solution or too much overspray will initiate a stripping action on the floor finish.
- While the floor is still damp from Super Spraybuff, make several passes with a floor machine using a synthetic buffing pad. The floor will immediately become dull and smeared but continued buffing will dry the surface and produce a brilliant gloss.
- Difficult to remove marks and scuffs should be sprayed and buffed again.
- Pads should be changed as they fill up, otherwise the accumulated soil will be redeposited on the floor.
- It is not always necessary to spray buff the entire floor, only the high traffic areas are important.

1. Remove gum, loose soil, paper, etc. and dust mop. Damp mopping is recommended when floor is heavily soiled. Floor should be absolutely dry before applying Super Spraybuff.
2. For heavily trafficked and worn areas use Super Spraybuff full strength.
3. For routine repair and economy, dilute Super Spraybuff with one part cool water.
4. Using a trigger sprayer or other appropriate equipment, apply Super Spraybuff sparingly about two to three machine widths wide. Move machine back and forth sprayed area to clean. Repeat pass to polish.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Total Active Solids – 20.5%
 Specific Gravity - .92 @ 24°C/75°F
 pH (Concentrate) - 9.0 – 9.5

Stability

- a. Storage @ 24°C/75°F - One year minimum
- b. Accelerated @ 52°C/125°F - 60 days minimum
- c. Freeze/Thaw - Can withstand three cycles

PACKAGING

445060	275-gallon totes
445055	55-gallon drum
445030	30-gallon drum
445015	15-gallon drum
445005	5-gallon pail
445004	1-gallon (4 per case)



Label copy is provided in English and Spanish. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Distributed by: