



# FiberPRO<sup>®</sup> FOAM CONTROL



## Low Foam Extraction Cleaner

This highly concentrated product quickly penetrates and knocks down foam to eliminate problems associated with recovery tank foaming.

### Uses

- Recommended for use in recovery tanks of extraction machines or automatic scrubbers where foaming might be a problem.
- Carpet extraction recovery tanks.
- Automatic scrubber recovery tanks.
- Sewage systems.
- Water fountains.
- Whirlpools.

### Features

- Fast Acting - Breaks foam on contact.
- Saves Time - Eliminate downtime and wasted effort in dumping recovery tanks.
- Versatile - Has many uses, can be used anywhere foaming is a problem.

### Properties

Color .....Milky white  
 Dilution .....Use as necessary, until foam subsides  
 Flash point..... None  
 Fragrance ..... Characteristic  
 pH ..... 7.0 - 8.0



### Directions For Use

**Read the entire label before using this product.**

Shake or mix container well before using. EXTRACTORS OR AUTOMATIC SCRUBBERS: Initially place 1 oz. of defoamer per gallon capacity of the pick up tank (8 mL/L) 1:128. If carpet is full of shampoo from previous cleanings, more defoamer may be needed. SEWAGE SYSTEMS OR WATER PLANTS: Add defoamer, wait a few minutes for it to disperse, continue until suds subside.

### Safety

Keep out of reach of children. For institutional and commercial use. **CAUTION:** Contains emulsifiers. May cause eye irritation. Avoid contact with eyes. **FIRST AID:** If splashed on skin, wash with soap and water. If splashed in eyes, flush with large quantities of water. If swallowed, dilute with two glasses of water. Call a physician.

### Available In

Case/ 4 - 1 Gallon (3.78 L): #40304-00  
 Drum/55 Gallon (208 L): #40355-00

