



# On an' On<sup>®</sup>

## high solids metal interlock floor finish

On an' On's special formulation greatly reduces the probability of powdering, even under unfavorable conditions such as low humidity and high heat.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.  
1110 Spartan Drive  
Maumee, OH 43537  
1-800-537-8990  
www.spartanchemical.com

#### SUPERIOR LEVELING:

Leveling relates to a product's surface tension and the ability of a finish to flow smoothly and evenly. Spartan has developed a unique formulation for On an' On which assures a smooth, even application and provides an ease of repairability that's uncommon in other high solids finishes.

#### HIGH SOLIDS:

On an' On with 25% non volatile solids, provides nearly twice as much protection per coat of conventional finish and reduces in use costs to the customer. The customer will save money in the long run as two coats of non buff On an' On provides the beauty and protection of three or more coats of a standard finish.

#### SCUFF RESISTANT:

Because of the high solids content, On an' On is highly resistant to black heel marks and scuffing. The surface marks which may appear can be easily spray buffed away.

#### DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and SDS. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

#### INITIAL APPLICATION:

1. Completely strip all old wax or floor finish. Depending upon build-up, use hot water and a Spartan Stripper.
2. Remove all stripping solution and follow with two to three clear water rinses. Allow to dry.
3. Apply two coats of a Spartan seal.
4. Apply On an' On in a uniform, thin coat. Let dry thoroughly for 30 to 40 minutes, until surface is dry to the touch. Apply subsequent coats in the same manner.

#### MAINTENANCE:

**Routine:** Dust mop or sweep floor as necessary.

**Periodic:** Dust and damp mop using one of Spartan's cleaners. To easily repair traffic areas between finish applications, use a Spartan restorer or spraybuff. (Traffic lanes may be re-coated as necessary.) For heavily-soiled areas, machine scrub using the recommended dilution of one of the above-mentioned cleaners.

**As Needed:** Dust mop floor and scrub. Reapply On an' On.

**Annual:** Deep scrub and recoat; or completely strip, reseal and reapply floor finish.

**NOTE:** For best results always use Spartan floor cleaners and strippers.



**Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting [www.spartanchemical.com](http://www.spartanchemical.com).**

#### SPECIFICATIONS:

Total Solids: 31.7%

Non-volatile Solids: 25.0%

pH: 8.6 – 8.9

Stability:

- a. Storage @ (24°C/75°): 1 year minimum
- b. Accelerated @ (52°C/125°F): 60 days minimum
- c. Freeze/thaw Cycle: Will withstand 3 cycles

Gloss (Gardner): 90 – 93

#### COVERAGE:

Up to 3,000 square feet per gallon depending on application method and porosity of floor.



**ISSA** MEMBER  
The Experts  
on Cleaning and Maintenance

Distributed by:

#### PACKAGING

547355	55-gallon drum
547305	5-gallon pail
547304	1-gallon (4 per case)



Label copy is provided in English, Spanish, and French. Secondary labels are also available.

**GUARANTEE:** Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product Available Worldwide. For institutional and industrial use only.

© SCC 01/25 L5473