

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory-Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

RESTORE 77

Note: Blank spaces are not permitted. If any item is not applicable, or
no information is available, the space must be marked to indicate that.

Section I

NA = Not Applicable NIA = No Information Available

Manufacturer's Name

Sunburst Chemicals, Inc.

Emergency Telephone Number

1-866-303-6943 (7 days/24 hours)

Address (Number, Street, City, State, and ZIP Code)

220 W. 86th St.

Telephone Number For Information

(952) 884-3144

Bloomington, MN 55420

Date Prepared

05-26-11

Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))

OSHA PEL
%(optional)

ACGIH TLV

Other Limits
Recommended

Sodium Hydroxide

2mg/m³

2mg/m³

Section III – Physical/Chemical Characteristics

Boiling Point

NA

Specific Gravity (H₂O= 1)

NA

Vapor Pressure (mm Hg.)

NA

Melting Point

NIA

Vapor Density (AIR= 1)

NA

Evaporation Rate
(Butyl Acetate = 1)

NA

Solubility In Water

Up to 10%.

Appearance and Odor

Off white granular powder, low odor.

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)

None.

Flammable Limits

LEL

NA

UEL

NA

Extinguishing Media

Water, CO₂, Dry chemical.

Special Fire Fighting Procedures

None.

Unusual Fire and Explosion Hazards

None.

HMIS		NFPA			
3	HEALTH	HEALTH HAZARD	FIRE HAZARD	SPECIFIC HAZARD	REACTIVITY
0	FLAMMABILITY	4 Deadly	4 Below 73° F (Boiling pt. below 100° F)	Oxidizer OX	4 May detonate
0	REACTIVITY	X 3 Extreme danger	3 Below 73° F (Boiling pt. at/above 100° F)	Acid ACID	3 Shock and heat may detonate
B	PERSONAL PROTECTION	2 Hazardous	And/or at/above 73° F - not exceeding 100° F	Alkali ALK	2 Violent chemical change
		1 Slightly hazardous	2 Above 100° F, Not Exceeding 200° F	X Corrosive COR	1 Unstable if heated
		0 Normal material	1 Above 200° F	Use NO WATER	X 0 Stable
			X 0 Will not burn	Radioactive	

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	
Incompatibility (<i>Materials to Avoid</i>) None.			
Hazardous Decomposition or Byproducts None.			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI – Health Hazard Data

Routes(s) of Entry:	Inhalation? NO	Skin? NO	Ingestion? NO
Health Hazards (<i>Acute and Chronic</i>) <u>ACUTE</u> - irritation to eyes and skin, distress to digestive tract, diarrhea, chemical burns. <u>CHRONIC</u> - NIA.			
Carcinogenicity:	NTP? NIA	IARC Monographs? NIA	OSHA Regulated? NIA
Signs and Symptoms of Exposure <u>EXTERNAL</u> - redness of skin or eyes, burning sensation, chemical burns. <u>INTERNAL</u> - foul taste, burning sensation in mouth and throat, poisoning.			
Medical Conditions Generally Aggravated by Exposure Open sores or wounds.			
Emergency and First Aid Procedures <u>EXTERNAL</u> - thoroughly rinse with water for at least 15 minutes. Get medical attention if irritation persists. <u>INTERNAL</u> - drink a large quantity of milk or water. Get immediate medical attention.			

Section VII – Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Absorb spilled material with an absorbent material such as clay, sawdust, or sand. Sweep up as much of this as possible and place in a sealed, labeled container or in a proper landfill. Thoroughly rinse the affected area with water.	
Waste Disposal Method Spilled material should be collected as above for disposal in a landfill according to Federal, State, and Local regulations. Any rinsing of the affected area should also be in accordance with Federal, State and Local regulations.	
Precautions to Be Taking in Handling and Storing Keep tightly closed when not in use.	
Other Precautions Avoid contact of product (or its use solutions) with skin, eyes or clothing. Caustic alkaline material - corrosive.	

Section VIII – Control Measures

Respiratory Protection (<i>Specify Type</i>) Not required.		
Ventilation	Local Exhaust NA	Special NIA
	Mechanical (<i>General</i>) NIA	Other NIA
Protective Gloves Rubber or vinyl recommended.		Eye Protection Safety glasses, goggles recommended.
Other Protective Clothing or Equipment Rubber apron.		
Work/Hygienic Practices Always wash hands after handling.		