



TRENDSETTER PRO™

Sealer and Finish



Trendsetter Pro is a 20% solids sealer and finish based on a blend of proven, optically enhanced acrylic polymers that produce a durable high gloss finish that can extend the time between strip and recoats. Designed for maintenance with high-speed and UHS (Ultra High Speed) equipment, Trendsetter Pro produces high off the mop gloss with a long-lasting burnish response—a balance of properties ideal for high traffic floors.

TRENDSETTER PRO™

FEATURES

- 20% non-volatile solids, high-gloss, burnishable finish
- Built on a blend of premium, optically enhanced polymers designed for high-speed burnishing maintenance routines
- Designed for use in high-traffic areas
- Excellent application properties such as forgiving wetting, leveling, and tolerance to high humidity conditions

BENEFITS

- Lowers labor costs by reducing the frequency of restorative maintenance procedures such as top scrubbing/stripping and recoating
- Enables successful application for all levels of experience
- Creates a clear, wet-look gloss appearance that is easily maintained
- Reduces the need for multiple products to seal and finish a floor

SPECIFICATION DATA

Dilution	Ready-to-use
pH	8.0 – 9.0
Color	Translucent
Fragrance	Slight ammonia
Specific Gravity @ 24°C/75°F	1.033
Total Solids	25.7%
Flash Point	> 100°C / > 212°F ASTM D56
Stability: Shelf @ 24°C/75°F	18 months
Stability: Freeze/Thaw	Will withstand 3 cycles

DIRECTIONS FOR USE

PREPARATION

Completely strip all floor finish. Depending upon buildup, use warm or room temperature water (80°F – 120°F or 27°C – 49°C) and a Spartan stripper. Remove the stripping solution and either follow with Shinline Floor Prep or two to three clear-water rinses. Allow to dry.

SEAL/FINISH

Apply Trendsetter Pro in a uniform, thin coat. Let dry thoroughly (30 to 40 minutes depending on temperature, humidity and ventilation). Apply subsequent coats in the same manner. Five coats are recommended for initial application.

MAINTENANCE

Always dust mop and/or damp mop before burnishing floor. Burnish as necessary depending on traffic to repair minor scratches and enhance gloss. Deep scrub as required and rinse with clear water prior to recoating. Depending on machine type and speeds, experiment with buffing pads for quick touch-ups of high traffic or "first impression" areas.

ORDERING INFORMATION



#501004 #501005 #501055

ADDITIONAL RESOURCES

Scan the QR code to access this product's safety information and documentation.



SAFETY: For institutional and industrial use only. Be sure to read all directions, precautionary and first aid statements on product labels before using this or any other Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor and at www.spartanchemical.com. Workplace labels are available in English, Spanish, and French.

GUARANTEE: Spartan's modern manufacturing and laboratory control ensures uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within 12 months of the date of manufacture.