

Enzyme Digester Drain Maintainer

DESCRIPTION

This product is a safe, bioactive blend, which attacks organic solids such as greases, fats, proteins, and carbohydrates, destroying malodors at their source. It is recommended for use in grease traps, septic systems, drain lines, refuse containers, and all areas where organic solids are the cause of malodor problems.

Please read entire container label for detailed instructions and safety information.

DIRECTIONS

GREASE TRAPS: Start treatment immediately after grease trap has been pumped. For 20 cubic feet or less, pour 32 oz. of product into opening closest to trap during least active time. For maintenance, add 5 - 10 oz. of product daily. For larger traps, use 32 oz. per 20 cu.ft., then add 8 - 12 oz. for daily maintenance.

DRAIN LINE / DOWN PIPES: Treat line with 4 - 8 oz. of product for every two inches of pipe diameter. Start treatment on first floor and work up. Use 2 - 4 times weekly depending on usage.

SEPTIC TANKS: Flush 16 oz. of product per 25 cu.ft. capacity through toilet for initial treatment and 8 oz. per week for maintenance. For severe problems add 1 gallon initially.

PORTA-TOILETS: Add 1 gallon of product directly and cover with water to aid digestion.

REFUSE CONTAINERS / DUMPSTERS: Dump container. Rinse with water and spray surface with a 1:1 mixture of product and water.

FEATURES

- · Bio-active
- Multiple bacteria strains
- Stabilized excess enzymes
- Can be automatically dispensed

ADVANTAGES

- Attacks all organic wastes
- Removes malodors at their source
- · Eliminates measurement errors

BENEFITS

- Safe to plumbing
- Starts breaking down organic wastes on contact
- Highly effective deodorant

SPECIFICATIONS

Color	Red
Fragrance	None
pH Range	7.0- 7.5
Dilution	RTU
Density	8.42

REORDER#

K000744/1	gallon
K000755	gallon

victoriabayproducts.com | 255 Route 1 & 9, Jersey City, NJ 07306 | (800) 535-5053