

Endura STRIP

finish and wax stripper

EnduraSTRIP is an intense remover, originally developed for Spartan's very durable Endura Gloss finish. This stripper removes heavy build-up even in your hard to strip areas. EnduraSTRIP is concentrated for economy and flexibility.





Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee, OH 43537 1-800-537-8990 www.spartanchemical.com

AGGRESSIVE STRIPPING ACTION!

EnduraSTRIP is a powerful blend of select solvents chosen for their ability to quickly attack and remove heavy finish build-up. The formula is unique in the fact that it does not emulsify like a normal floor finish stripper. Instead, EnduraSTRIP quickly penetrates and actually lifts the finish off the floor. Pickup with a wet-vac or auto scrubber and clear water rinse to remove residue. Flood rinsing is not necessary.

ECONOMICAL:

EnduraSTRIP is highly concentrated and is formulated to be diluted. Easily achieve equivalent removability as a conventional floor stripper with half the amount of EnduraSTRIP.

PLEASANT TO USE:

EnduraSTRIP does not contain added fragrance. When diluted for use, it is virtually odor-free. In addition, EnduraSTRIP only contains low level VOCs.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Prevent pedestrian traffic with signs or barricades.

Light to Medium Finish/Wax Build-up:

Dilute product up to 1:12 (10 oz./gal.) or (83 ml per liter) with warm or room temperature water.

Heavy Finish Build-up:

Dilute up to 1:8 (16 oz./gal.) or (125 ml per liter). Liberally apply product with mop to small section (100 sq.ft./9 m²) of floor. Be sure to completely cover floor to the baseboards. After 3 to 5 minutes, begin to agitate the floor with a floor machine using a stripping brush. Additional stripper solution may need to be added to keep the floor wet. Pick up solution using wet-vac. Use of an automatic scrubber is an alternative.

NOTE: Do not allow solution to dry on the floor. Clear water rinse two or three times to remove residue or squeegee tracks as necessary. Flood rinsing is not required before recoating.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.



SPECIFICATIONS:

Total Active Ingredients - 50%
Specific Gravity - 1.025
Density - 8.538 lbs/gal
Viscosity - water thin
pH Concentrate - 13.4 - 13.8
Flash Point (Cleveland Open Cup) - 210°F

- a. Shelf @ 24°C/75°F in excess of one year
- b. Accelerated @ 49°C/120°F in excess of 90 days
- c. Freeze/Thaw Cycle freezes and thaws with complete clarity

Rinsability - rinses completely in hot or cold water

Biodegradable Phosphate free

Stability:



PACKAGING		
006760	275-gallon totes	
006755	55-gallon drum	
006730	30-gallon drum	Laminate Lights EnduraSTR
006715	15-gallon drum	Emiliate Stripper Limitate Stri
006705	5-gallon pail	
006704	1-gallon (4 per case)	Decapate de Laminado Servicio de la companio del companio de la companio del companio de la companio del companio de

Label copy is provided in English and Spanish. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.