



Features

- H.264 and H.265 video streams
- 4K, 5MP, 4MP, 3MP, 2MP, 1.3MP, 1MP recording resolution
- 4ch 4MP real time live view, 4ch 8MP realtime recording, 4ch 4MP real time Playback
- Multiple selectable recording modes (continuous, motion detection and event)
- ONVIF Version 2.3 conformance
- 4 independent 48V PoE network ports
- Supports 2*HDD, each up to 8TB
- Front panel control
- VGA and HDMI video outputs
- 4ch alarm input, and 1ch alarm output
- 1-ch Audio Output(RCA)
- Operating Temperature: 14°~131°F/-10°~ 55°C
- CE, FCC, RoHS
- Comes with a 36-month warranty
- Web client support Internet Explorer, Firefox, Chrome, Safari
- PC Client support Win7 Win8 Win10 and MAC
- Free mobile app for remote viewing of live and recorded video (iOS and Android)
- Infilux P2P enabled.
- Power supply built in the chassie
- 1 USB 2.0 and 1 USB 3.0 ports, E-SATA
- Provide IE ActiveX, CMS, StreamView APP
- Max Bandwidth: 50Mbps

Ordering information

F81-A0204-P4

4ch network camera video access,
2 SATA HDDs, each HDD up to 8TB, no
Hard disks, 1 HDMI (up to 4K), 1 VGA,
4ch alarm in, 1ch alarm out,
4 PoE ports,
DC 48V

F81-A0204-P4-1T

4ch network camera video access, with
Hard disks, Supports 1TB of total
storage capacity

F81-A0204-P4-2T

4ch network camera video access, with
Hard disks, Supports 2TB of total
storage capacity

F81-A0204-P4-4T

4ch network camera video access, with
Hard disks, Supports 4TB of total
storage capacity

Technical specifications

| | |
|----------------------------------|---|
| Model | F81-A0204-P4 |
| Recording Bandwidth | Max 50Mbps |
| Recording Resolution | 8MP(4K), 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P) |
| Display Split | 1/4 |
| Live/Playback Performance | 4K: 1ch realtime 4MP/3MP/2MP: 4ch realtime |
| Output Interface | 1 HDMI (up to 4K), 1 VGA |
| Display Resolution | 1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 1680*1050, 1600*1200, 1900*1200, 2560*1440, 3840*2160 |
| Alarm Input/Out | 4ch in / 1ch out |
| Ethernet | RJ-45 port (1000M) |
| Smart Phone | iOS, Android |
| Internal HDD | 2 SATA HDDs, each HDD up to 8TB |
| RS485 | yes |
| e-Sata | yes |
| Line In | yes |
| USB | 1x 3.0 USB for backup/upgrade, 2x 2.0 USB for mouse |
| ONVIF | ONVIF Version 2.3 conformance |
| POE | 4 PoE ports |
| Power Supply | DC48V, PoE Swith: 48V |
| Dimension (W×D×H) | 380*340*50mm (15in x 13.4in x 2in) |