

# HOLDRITE®

CONVERTING MAKESHIFT METHODS INTO ENGINEERED SOLUTIONS<sup>SM</sup>

## HOLDRITE® STRUT CLAMPS

**HOLDRITE® FLAME FIGHTER™**

**NEW OVERHEAD  
PLENUM-RATED  
PRODUCT SOLUTIONS**



- Multi-Size Clamps Hold up to 2" CTS/IPS
- Eliminates the Need for Over 20 SKUs
- Compatible with Copper, PEX, CPVC, CSST, Steel and Cast Iron Pipe
- Significantly Reduces Installation Costs
- No Tools, Easy to Install



Patents Pending

### HOLDRITE® SILENCER™ SYSTEM



### IDEAL SOLUTIONS

HOSPITAL



HIGH RISE



**YELLOW = ASTM E-84 25/50 (Plenum Rated)**

**BLUE = UL94V-2 (Flame Rated)**

**WHITE = ISO-3822 LAB TESTED  
(Acoustical Noise & Vibration Isolation)**

Model #	Pipe Size	Load Rating Suspended	Load Rating Top Mount	Temperature Range
257-S	Up to 1" CTS	25 lbs	200 lbs	-20°F to 200°F
257/257-P	Up to 1" CTS	25 lbs	200 lbs	-10°F to 180°F
287-S	1" - 2" CTS/IPS	75 lbs	300 lbs	-20°F to 200°F
287/287-P	1" - 2" CTS/IPS	75 lbs	300 lbs	-10°F to 180°F

### INSTALLATION INSTRUCTIONS - INSTALLS IN SECONDS



(800) 321-0316 • [www.holdrite.com](http://www.holdrite.com)

# HOLDRITE® EZ-STRUT™

## HOLDRITE® FLAME FIGHTER™



- Eliminates the Need to Cut Strut
- Integrates with HOLDRITE® Clamps
- Ideal for Medical Gas Lines
- Ideal for Supporting up to 2" CTS/IPS



**YELLOW = ASTM E-84 25/50 (Plenum Rated)**  
**BLUE = UL94V-2 (Flame Rated)**  
**WHITE = ISO-3822 LAB TESTED**  
 (Acoustical Noise & Vibration Isolation)

Model #	Length	Rating (lbs)
EZ-1	12"	1000
	18"	500
	21"	360
EZ-2	23"	400
	30"	400
	36"	160
	40"	120



### HOLDRITE® FLAME FIGHTER™ CLAMPS ASTM E-84 25/50 (Plenum Rated)

MODEL#	DESCRIPTION	BOX QTY
250-S	ASTM E-84 25/50 PLENUM RATED. Mounts on EZ-1 and Stout Brackets. Variable closure clamp supports up to 1" CTS.	50
255-S	ASTM E-84 25/50 PLENUM RATED. Mounts directly to flat surface. Variable closure clamp supports up to 1" CTS.	50
257-S	ASTM E-84 25/50 PLENUM RATED. Mounts to standard strut with no tools. Variable closure clamp supports up to 1" CTS.	50
280-S	ASTM E-84 25/50 PLENUM RATED. Mounts on EZ-1 and Stout Brackets. Variable closure clamp supports 1" - 2" CTS/IPS.	50
285-S	ASTM E-84 25/50 PLENUM RATED. Mounts directly to flat surface. Variable closure clamp supports 1" - 2" CTS/IPS.	50
287-S	ASTM E-84 25/50 PLENUM RATED. Mounts to standard strut with no tools. Variable closure clamp supports 1" - 2" CTS/IPS.	50

### HOLDRITE® SILENCER™ SYSTEM CLAMPS ISO-3822 LAB TESTED (Acoustical)

MODEL#	DESCRIPTION	BOX QTY
250	NOISE & VIBRATION ISOLATION PADS. UL94V-2 flame-rated framework. Mounts on EZ-1 and Stout Brackets. Variable closure clamp supports up to 1" CTS.	50
255	NOISE & VIBRATION ISOLATION PADS. UL94V-2 flame-rated framework. Mounts directly to flat surface. Variable closure clamp supports up to 1" CTS.	50
257-P	NOISE & VIBRATION ISOLATION PADS. UL94V-2 flame-rated framework. Mounts to standard strut with no tools. Variable closure clamp supports up to 1" CTS.	50
280	NOISE & VIBRATION ISOLATION PADS. UL94V-2 flame-rated framework. Mounts on EZ-1 and Stout Brackets. Variable closure clamp supports 1" - 2" CTS/IPS.	50
285	NOISE & VIBRATION ISOLATION PADS. UL94V-2 flame-rated framework. Mounts directly to flat surface. Variable closure clamp supports 1" - 2" CTS/IPS.	50
287-P	NOISE & VIBRATION ISOLATION PADS. UL94V-2 flame-rated framework. Mounts to standard strut with no tools. Variable closure clamp supports 1" - 2" CTS/IPS.	50

### HOLDRITE® STRUT CLAMPS UL94V-2 (Flame Rated)

MODEL#	DESCRIPTION	BOX QTY
257	UL94V-2 FLAME RATED FRAMEWORK. Mounts to standard strut with no tools. Variable closure clamp supports up to 1" CTS.	50
287	UL94V-2 FLAME RATED FRAMEWORK. Mounts to standard strut with no tools. Variable closure clamp supports 1" - 2" CTS/IPS.	50

### HOLDRITE® BRACKETS

MODEL#	DESCRIPTION	BOX QTY
EZ-1	Galvanized steel telescoping trapeze platform extends 12"- 21" and supports up to 1000 lbs.	50
EZ-2	Galvanized steel telescoping trapeze platform extends 23"- 40" and supports up to 400 lbs.	50
SB1S	Telescoping galvanized steel bracket extends 10" - 18". Ideal for lavatory, shower, water closet, vertical and horizontal applications. Screws included.	50
SB2S	Telescoping galvanized steel bracket extends 13" - 25". Ideal for lavatory, shower, water closet, vertical and horizontal applications. Screws included.	50

### HOLDRITE® ISOLATORS & STANDARD CLAMPS ASTM E-84 25/50 (Plenum Rated)

MODEL#	DESCRIPTION	BOX QTY
424-S, 425-S, 426-S	ASTM E-84 25/50 PLENUM RATED. Isolators for #121 & #125 series brackets. Supports 1/2", 3/4", and 1" CTS.	25
221-S, 222-S	ASTM E-84 25/50 PLENUM RATED. Suspension clamps. Supports 1/2" & 3/4" CTS.	100
231-S, 232-S	ASTM E-84 25/50 PLENUM RATED. Standard clamps. Supports 1/2" & 3/4" CTS.	100