



SURE-VENT® AIR ADMITTANCE VALVE WALL BOX



TECHNICAL SPECIFICATION: Sure Vent Air Admittance Wall Box can be used with a 6 or 20 DFU Air Admittance Valve requiring a recessed installation. Sure Vent AAV Wall Box accommodates 1-1/2" or 2" adapters through box opening and provides a high impact polystyrene textured grille faceplate to conceal the AAV.








Materials and Dimensions

- Box High Impact Polystyrene
- Faceplate High Impact Polystyrene (Textured)

Features

- Polystyrene grille faceplate allows air movement to the Sure-Vent while the box offers protection and access to the Sure-Vent behind the drywall.
- Grille is attached to the box frame by using Snap In "Tooth and Groove" mechanism.
- Box has two mounting brackets to secure it to the studs.
- AAV mounts inside the wall box to the DWV system via a 2" diameter molded-in drain port.
- Box will accommodate AAV with 1-1/2" or 2" adapter.
- Sure-Vent Air Admittance Valve sold separately.



\checkmark	PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
	39260	Sure Vent 4-1/2" x 5-3/4" Wall Box w /20 DFU AAV & PVC Adapter	6	lbs.
	39261	Sure Vent 4-1/2" x 5-3/4" Wall Box w/ 20 DFU AAV & ABS Adapter	6	lbs.
	39262	Sure Vent 4-1/2" x 5-3/4" Wall Box w/ Louvered Faceplate	6	lbs.
	39263	Sure Vent 4-1/2" x 5-3/4" Wall Box Louvered Faceplate	6	lbs.

Data is subject to manufacturing tolerances.