

# **Threaded Brass Manifold Straight Adapter**

Submittal Information Revision B: July 19, 2010

# Project Information

Job Name:


30b Name.			
Location:	Part No. Ordered:		
Engineer:	Date Submitted:		
Contractor:	Submitted By:		
Manufacturer's Representative:	Approved By:		

#### **Technical Data**

Material: C84400 Brass

Maximum Temperature (no pressure): 220°F (104°C)

Maximum Pressure: 125 psi (8.6 bar)



Fax: (800) 638-9517

www.uponor.ca

## **Product Information and Application Use**

The Uponor Threaded Brass Manifold Straight Adapter is used with TruFLOW™ manifolds. The adapter transitions the R32 manifold union nut to R20 and R25 threaded connections (PEX or Multi-layer Composite (MLC) tubing with QS-style fittings) in radiant heating and cooling applications.

✓	Description	Part Number	Α	В	С	D	Weight
	Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male	A4143220	1.75"	1.58"	R32	R20	0.55 lbs.
	Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male	A4143225	1.75"	1.60"	R32	R25	0.56 lbs.

## Installation

R32 threads into Uponor TruFLOW manifolds. For additional information, refer to the TruFLOW Manifold Instruction Sheet or the Radiant Floor Heating Installation Handbook.

#### **Standards**

ASTM F877

#### Codes

N/A

## Listings

NSF-rfh; R32: ISO 228-G 11/4 B

# Related Applications Contact Information Radiant Heating and Cooling Systems Snow and Ice Melting Systems Permafrost Protection Systems Turf Conditioning Systems Contact Information Uponor Ltd. 5925 148<sup>th</sup> Street West Apple Valley, MN 55124 USA Phone: (800) 321-4739 Phone: (888) 994-7726

Fax: (952) 891-2008

www.uponor-usa.com