

Application:  Outdoor

Installation Type:  Fixed

Certificate:  CE;  Rohs;  ETL;  FCC



### VN6 SPECIFICATIONS

Version: V20191106

	Parameter	Value	Unit
<b>Module</b>	Pixel Pitch	6.66	mm
	LED Type	SMD2727	/
	Module Size(WxH)	320x320	mm
	Pixel Per Module	48x48	Dots
	Module Weight	4.2	Lbs
<b>Panel</b>	Size	1280x960x96	mm
	Pixels	192×144	dots
	Material	Aluminum	/
	Weight	84	Lbs
	Brightness	8500	nits
	Processing depth	14~16	bit
	Display refresh rate	1920	Hz
	Color Temperature	3200~9300	K
	Viewing angle(H)	140 (70/70)	deg.
	Viewing angle(V)	105 (45/60)	deg.
	Drive type	1/4 Scan	/
<b>Application</b>	AC Operating Voltage	110/240	V
	AC Input Frequency	50/ 60	Hz
	Power Consumption (Max./Avg.)	750/250	W/m <sup>2</sup>
	Storage Temperature	- 40~ + 140	F
	Operating Temperature	- 4~ + 122	F
	Storage Humidity	10 % ~90 %	RH
	Operating Humidity	10 % ~90 %	RH
	IP Rating (Front/Rear)	IP65/IP54	/
	Module Maintenance	Front or Rear	/
	PSU & Others Maintenance	Front or Rear	/
	Panel Installation Type	Front or Rear Installation	/
	Maximum number of panel for Lifting	/	PCS

Remark: Power consumption tolerance: ±15%, according to the actual situation.

Vista Video Outdoor reserves the right to modify specifications and parameters without further notice.