



A1 FLOOR PLAN
A111 1/4" = 1'-0"

GENERAL NOTES

- WORK NOTED "BY OTHERS" OR "NIC" SHALL BE PROVIDED BY OWNER OR UNDER SEPARATE CONTRACT.
 - SEE SHEET A800 AND A301 FOR DOOR TYPES AND DETAILS.
 - PROVIDE CONTROL JOINTS ON GP. BD. ASSEMBLES PER SPECIFICATIONS AND WHERE SHOWN.
 - REVIEW DOCUMENTS AND VERIFY DIMENSIONS AND FIELD CONDITIONS WHEN APPLICABLE. CONFIRM THAT WORK IS BUILDABLE AS SHOWN. ANY CONFLICTS OR OMISSIONS SHALL BE IMMEDIATELY REPORTED TO THE ARCHITECT FOR CLARIFICATION PRIOR TO THE PERFORMANCE OF WORK IN QUESTIONS.
 - COORDINATE AND PROVIDE METAL OR RATED SOLID WOOD BLOCKING (FIRE TREATED) IN PARTITIONS AND CEILING FOR MILLWORK, WALL AND CEILING ATTACHED ITEMS AS SPECIFIED.
 - DO NOT SCALE DRAWINGS. WRITTEN DIMENSIONS GOVERN. ALL PARTITION LOCATIONS, DIMENSIONS AND TYPES, DOOR AND WINDOW LOCATIONS SHALL BE AS SHOWN ON PARTITION PLAN. IN CASE OF CONFLICT, NOTIFY ARCHITECT.
 - COORDINATE WITH TENANT AND OWNER THE SCHEDULE FOR TELEPHONE, DATA, SECURITY AND AUDIO VISUAL INSTALLATIONS.
 - PARTITIONS AT BUILDING PERIMETER SHALL BE CENTERED ON CENTER LINE OF COLUMN OR WINDOW MULLION, UNLESS NOTED OTHERWISE.
 - PROVIDE PARTITION TYPE WITH THE HIGHEST UL AND/OR ACUSTICAL PERFORMANCE RATING WHERE MORE THAN ONE PARTITION TYPE IS INDICATED. PARTITIONS SHALL BE PARTITION CONDITION "B" UNLESS OTHERWISE NOTED.
 - OFFSET ELECTRICAL AND TELEPHONE OUTLETS 16" MINIMUM IN SEPARATE STUD WALL CAVITIES.
 - USE MOISTURE & MOLD RESISTANT G.W.B. ON WET WALLS (FULL HEIGHT).
 - SEE SHEET A101 & A131 FOR ADDITIONAL INFORMATION.
 - WALL PARTITIONS TO BE 0G3B-S UNLESS NOTED OTHERWISE. SEE A010 FOR ADDITIONAL INFORMATION.
- AA. PUSH BUTTONS TO BE MOUNTED AT 40" ABOVE FINISH FLOOR. PATCH AND REPAIR AS NEEDED.
- BB. ALL ROOF-TOP EQUIPMENT IS TO BE SCREENED FROM VIEW AND MEET THE REQUIREMENTS OF THE TOWN OF PLAINFIELD.

LEGEND

- EXISTING WALL TO REMAIN
- NEW CONSTRUCTION
- OFFICE**
- 201** ROOM NAME & NUMBER
- NEW DOOR
- A: INDICATES ACTIVE LEAF
- HO: INDICATES ELECTRONIC HOLD OPEN
- EXISTING DOOR
- FEC SEMI-RECESSED FIRE EXTINGUISHER CABINET. REFER TO SHEET A010
- DOOR TYPE TAG
- ELEVATION TAG
- DETAIL TAG
- WALL TAG

PARTITION TAG LEGEND

- PARTITION RATING
 - PARTITION MATERIAL
 - NOMINAL WIDTH OF STRUCTURE
 - PARTITION HEIGHT CATEGORY
 - (EXTEND TO STRUCTURE IF NOT INDICATED)
 - PARTITION MODIFIER
- PARTITION RATING:**
- 0xxx NON-RATED
 - 1xxx 1-HOUR RATED
 - 2xxx 2-HOUR RATED
 - 3xxx 3-HOUR RATED
 - 4xxx 4-HOUR RATED
- PARTITION CONSTRUCTION:**
- xPxx FURRING
 - xGxx GYP / METAL STUD (OPERABLE)
 - xSxx SHAF
 - xMxx MASONRY
 - xWxx GYP / WOOD STUD
 - xExx EXISTING
- NOMINAL WIDTH OF STRUCTURE:** (SEE PARTITION STRUCTURE KEY)
- xxxx EXTEND TO STRUCTURE ABOVE
 - xxxB TERMINATE ABOVE CEILING
 - xxxC TERMINATE AT CEILING
 - xxxP PARTIAL HEIGHT PARTITIONS
- PARTITION MODIFIER:**
- A ABOVE ACCESS FLOOR
 - B BALLISTIC LEVEL RATED
 - E EXTRA LAYER OF GYPSUM
 - G GROUT MASONRY SOLID
 - I IMPACT RESISTANT
 - K SMOKE RATED
 - M METAL PANEL
 - O MOVABLE PARTITION
 - R MOISTURE RESISTANT
 - S SOUND ATTENUATION BATT
 - V VAPOR BARRIER
 - Z ACCENT WALL (SEE INTERIOR DETAILS)



ISSUE FOR PERMIT SET

ISSUE DATE: 01/29/25

REVISIONS:

NO.	REASON	DATE

PROJECT TEAM

PRINCIPAL IN CHARGE: CHARLES J. TODD
PROJECT MANAGER: STEVEN GARCIA
CIBRE PROJECT MANAGER: BETTY LEU
MODEL NAME: IN PLAINFIELD OPTUM

Location Code: IN 135
UHG #: K1116805
1192 EDWARDS DR.
PLAINFIELD, IN 46168
PARCEL #32-10-36-479-005-001-012

PROJECT NO.: 6722159700

SHEET TITLE: FLOOR PLAN

SHEET NUMBER: A111