OT66Q AT OUTDOOR TOWER SPEAKERS 6.5" WOOFER, 2-WAY, QUAD TWEETER, ULTRA-HIGH OUTPUT, OUTDOOR TOWER LOUDSPEAKER









32 h x 10 w x 7.3 d (in) (elliptical) 787 h x 254 w x 183 d (mm)

 $65Hz-24kHz \pm 3dB$

Frea Response Impedance Sensitivity Power rea.

Woofer/Tweeter: 4 Ohm 95dB 2.83V/1m

Woofer/Tweeter: 100W-300W Woofer/Tweeter (70V): 100W (2) 6.5" (165 mm) Aluminum Cone

Woofer Tweeter Finishes

(4) 1" (25 mm) Titanium Marine Powder Coat

cert-level performance outdoors. The OT66Q is the smaller Outdoor Tower speaker in the series, features a titanium guad array tweeter and dual aluminum 6.5" woofers for wide dispersion and crisp fidelity. Their robust engineering and design allow the James Loudspeaker AT Outdoor Tower speakers to effortlessly deliver high SPL playback over extended periods of time.

Any AT Outdoor Tower speaker can be installed using our internal mount (a beautifully hidden mounting solution for permanent installation into hardscape), or external mount (Add 0.25in or 6.4mm to height for EM) (a wider mounting plate, best suited for permanent landscape installations, or for moveable hardscape installations). For simplified installation and configuration, James Loudspeaker offers optional custom wiring harnesses. The speaker also has access through the front grille for easy in-field servicing.

> Each AT Outdoor Tower may be ordered in low impedance or 70V configurations. Can be built to custom height, up to 96" (32" minimum). Available in 10 standard finishes or infinite custom finishes options.

Mounting Options:



2185 Park Place, Minden, NV 89423 Ph: 775.461.7500 www.jamesloudspeaker.com



