## FXC620S CEILING SERIES 6.5" 2-WAY CEILING SPEAKER - SQUARE GRILLE





Size 9.15 dia x 6 d (in) 232 dia x 152 d (mm)

Freq Response 70Hz-20kHz±3dB

Impedance 4 ohms

Sensitivity 90dB 2.83V /1m

Power req. 25-150 watts

Woofer (1) 6.5" (165 mm) Aluminum

Tweeter (1) 0.75" (19 mm) Aluminum

Enclosure Aluminum

Finishes White Paintable Grille

PCB FXC620S-PB

The FXC620S ceiling speaker features a traditional 3/8" mounting flange, but by using a thin aluminum material instead of plastic, the speakers provides a flush mounted look – a preferred visual for many clients.

The FXC620S, small-format loudspeakers feature a coaxially mounted 0.75" aluminum dome tweeter design over a proprietary high-excursion 6.5" woofer. The FXC line was inspired by the successful SXC in-ceiling speakers, and intended for smaller spaces like kitchens, bathrooms and hallways where a James SA Series speaker is not needed. These speakers are enhanced when paired with a James subwoofer such as the QXC10S or QXC8S.

All woofers are James designed with aluminum cones and santoprene surrounds to allow marine use while maintaining the highest quality sound. All enclosures are constructed with aircraft grade 5052 aluminum and include white paintable aluminum grilles.

Installation could not be easier for either retro-fit or new construction projects.

For marine applications, use the FXC620SM. 70V options available.



535 Airpark Road, Napa, CA 94558 Ph: 707.265.6343 www.jamesloudspeaker.com