

DUAL AUGER GRAIN CARTS

SPECIFICATIONS

Model	1105	1205	1305	1500
Capacity When Equipped With Tracks	1300 bushels	1400 bushels	1500 bushels	1700 bushels
Capacity When Equipped With Flotation Tires	1250 bushels	1350 bushels	1450 bushels	NA
Unload Speed	Up to 750 bushels per minute			
Auger Description and Sizes	Dual auger, corner unloading with 24" diameter vertical auger and 22" diameter horizontal auger			
Auger Movement	Adjusts over 2' in height and nearly 2' in reach			
Auger Spout	Hydraulically adjustable 14 degrees up and down			
Short Side Height	11' 4"	10' 10"	11' 4"	11' 4"
Tires	Flotation & Row Crop	Flotation & Row Crop	Flotation & Row Crop	NA
Tracks	Camso	Camso	Camso	Kinze
Tarp	Manual or Electric	Manual or Electric	Manual or Electric	Manual or Electric
Electronic Scale Packages	Yes	Yes	Yes	Yes
Hydraulic Requirements	2 SCVs with joystick controller			

DUAL AUGER GRAIN CARTS

COMPETITIVE CAPACITY* COMPARISON

* All capacities shown in bushels.

** All carts in comparison are dual auger.

Cart Models**	—	1105	1205	1305	1500
Kinze Cart Equipped With Tracks	—	1300	1400	1500	1700
Kinze Cart Equipped With Flotation Tires	—	1250	1350	1450	NA
Brent 1196	1100				
Brent 1396		1300			
Brent 1596				1500	
J&M 1132	1150				
J&M 1432				1450	
J&M 1832					1800
Unverferth 1110	1100				
Unverferth 1310		1310			
Unverferth 1610					1600
Parker 1348		1325	1325		
Haulmaster 1100	1100				
Haulmaster 1300		1300			
Haulmaster 1600					1600
Kilbros 1111	1100				
Kilbros 1311		1300			
Kilbros 1611					1600
Balzer 1450				1450	
Balzer 1700					1700

Sept. 19, 2019

Cart capacity is based on #2 corn at 15% moisture (56 lb test weight). Cart capacity may vary based on crop type, grade, moisture and other environmental factors.

