

1105

Heaped Capacity - Tires: 1250 bushels¹
Heaped Capacity - Tracks: 1300 bushels¹
Unloads: 750 bu/min²



DIMENSIONS

Weight

Flotation (Empty)	24,900 lbs.
Row Crop (Empty)	27,500 lbs.
Track (Empty)	31,000 lbs.
Hitch (Empty)	3,950 lbs.
Hitch (Loaded) ¹	6,280 lbs.

Width – Overall

Flotation	14'
Row Crop 30"	12' 7"
Row Crop, Wide Row	15' 4"
Track	13'

Height – Overall

11' 4"

Length – Overall

31' 7"

SPECIFICATIONS

Vertical Auger	24" Diameter
Horizontal Auger	22" Diameter
Drive Belts	4-Band V Belts (2)

Flotation Tire

Hubs (Cast Ductile Iron)	20 Bolt
Spindle	4 ½"

Row Crop

Hubs (Cast Ductile Iron)	4–10 Bolt
Spindle	4 ½"

Camso Track System

Track Width	36"
Ground Contact Length	100"
Total Footprint (sq. in.)	7,214
End Wheels (Per Track)	(2) 31 ½"
Mid Wheels (Per Track)	4

Other

PTO	1 ¾" - 1000 rpm
Safety Chains (Grade 70)	(2) 40.5K lbs. Rated
Adjustable Discharge Spout	28 Degrees
Hydraulic Requirements	2 SCVs



1205/1305

Heaped Capacity - Tires: 1350 bushels¹ / 1400 bushels¹
 Heaped Capacity - Tracks: 1450 bushels¹ / 1500 bushels¹
 Unloads: 750 bu/min²

DIMENSIONS

Weight	1205	1305
Flotation (Empty)	25,190 lbs.	25,400 lbs.
Row Crop (Empty)	28,260 lbs.	28,470 lbs.
Track (Empty)	31,470 lbs.	31,680 lbs.
Hitch (Empty)	4,000 lbs.	4,040 lbs.
Hitch (Loaded) ¹	6,540 lbs.	6,600 lbs.
Width – Overall		
Flotation	14'	14'
Row Crop 30"	12' 7"	12' 7"
Row Crop, Wide Row	15' 4"	15' 4"
Track	13'	13'
Height – Overall	10' 10"	11' 4"
Length – Overall	34' 11"	34' 11"

SPECIFICATIONS (1205 & 1305)

Vertical Auger	24" Diameter
Horizontal Auger	22" Diameter
Drive Belts	4-Band V Belts (2)
Flotation Tire	
Hubs (Cast Ductile Iron)	20 Bolt
Spindle	6"
Row Crop	
Hubs (Cast Ductile Iron)	4-10 Bolt
Spindle	4 ½"
Camso Track System	
Track Width	36"
Ground Contact Length	100"
Total Footprint (sq. in.)	7,214
End Wheels (Per Track)	(2) 31 ½"
Mid Wheels (Per Track)	4
Other	
PTO	1 ¾" - 1000 rpm
Safety Chains (Grade 70)	(2) 40.5K lbs. Rated
Adjustable Discharge Spout	28 Degrees
Hydraulic Requirements	2 SCVs



1500

Heaped Capacity: 1700 bushels¹
 Unloads: 750 bu/min²

DIMENSIONS

Weight	
Flotation (Empty)	N/A
Row Crop (Empty)	N/A
Track (Empty)	35,180 lbs.
Hitch (Empty)	5,250 lbs.
Hitch (Loaded) ¹	7,380 lbs.
Width – Overall	
Flotation	N/A
Row Crop 30"	N/A
Row Crop, Wide Row	N/A
Track	13'
Height – Overall	11' 4"
Length – Total:	38' 10"

SPECIFICATIONS

Vertical Auger	24" Diameter
Horizontal Auger	22" Diameter
Drive Belts	4-Band V Belts (2)
Flotation Tire	
Hubs (Cast Ductile Iron)	N/A
Spindle	N/A
Row Crop	
Hubs (Cast Ductile Iron)	N/A
Spindle	N/A
Track	
Track Width	36"
Ground Contact Length	108"
Total Footprint (sq. in.)	7,776
End Wheels (Per Track)	(2) 36 ½"
Mid Wheels (Per Track)	4
Other	
PTO	1 ¾" - 1000 rpm
Safety Chains (Grade 70)	(2) 40.5K lbs. Rated
Adjustable Discharge Spout	28 Degrees
Hydraulic Requirements	2 SCVs

¹ Cart capacity and hitch weight are based on #2 corn at 15% moisture (56lb test weight). Cart capacity and hitch weight may vary based on crop type, grade, moisture and other environmental factors. ² Bushels per minute may vary with moisture content of grain and/or PTO rpm.