

OPTIONAL FEATURES

STAY INFORMED AND PROTECT YOUR CROP

Choose from two Digi-Star electronic scale options. Dual Camera packages are available to easily see the rear of the cart and grain unloading. Carts come standard with a manual tarp and the option to choose a cab-operated electric tarp.



Digi-Star® Electronic Scale Package Options

- GT400
- GT560 with AutoLog™



Camera Monitoring System

- Dual cameras
- 9" display

2-YEAR WARRANTY

PROTECT YOUR INVESTMENT

Expect superior performance in the field and exceptional reliability, based on nearly a half-century of quality and craftsmanship. Every Kinze Dual Auger Grain Cart comes with the only 2-year warranty in the industry.



1105

Capacity: 1100 bushels¹
 Heaped Capacity: 1200 bushels¹
 Unloads: 750 bu/min²

DIMENSIONS

Weight	
Flotation (Empty)	24,900 lbs.
Row Crop (Empty)	27,500 lbs.
Track (Empty)	31,000 lbs.
Hitch (Empty)	3,950 lbs.
Hitch (Loaded) ¹	6,280 lbs.
Width – Overall	
Flotation	14'
Row Crop 30"	12' 7"
Row Crop, Wide Row	15' 4"
Track	13'
Height – Overall	
	11' 4"
Length – Overall	
	31' 7"

SPECIFICATIONS

Vertical Auger	24" Diameter
Horizontal Auger	22" Diameter
Drive Belts	4-Band V Belts (2)
Flotation Tire	
Hubs (Cast Ductile Iron)	20 Bolt
Spindle	4 ½"
Row Crop	
Hubs (Cast Ductile Iron)	4–10 Bolt
Spindle	4 ½"
Camso Track System	
Track Width	36"
Ground Contact Length	100"
Total Footprint (sq. in.)	7,214
End Wheels (Per Track)	(2) 31 ½"
Mid Wheels (Per Track)	4
Other	
PTO	1 ¾" - 1000 rpm
Safety Chains (Grade 70)	(2) 40.5K lbs. Rated
Adjustable Discharge Spout	28 Degrees
Hydraulic Requirements	2 SCVs

1305

Capacity: 1300 bushels¹
Heaped Capacity: 1400 bushels¹
Unloads: 750 bu/min²



DIMENSIONS

Weight	
Flotation (Empty)	25,400 lbs.
Row Crop (Empty)	28,470 lbs.
Track (Empty)	31,680 lbs.
Hitch (Empty)	4,040 lbs.
Hitch (Loaded) ¹	6,600 lbs.
Width – Overall	
Flotation	14'
Row Crop 30"	12' 7"
Row Crop, Wide Row	15' 4"
Track	13'
Height - Overall	
	11' 4"
Length - Overall	
	34' 11"

SPECIFICATIONS

Vertical Auger	24" Diameter
Horizontal Auger	22" Diameter
Drive Belts	4-Band V Belts (2)
Flotation Tire	
Hubs (Cast Ductile Iron)	20 Bolt
Spindle	6"
Row Crop	
Hubs (Cast Ductile Iron)	4-10 Bolt
Spindle	4 ½"
Camso Track System	
Track Width	36"
Ground Contact Length	100"
Total Footprint (sq. in.)	7,214
End Wheels (Per Track)	(2) 31 ½"
Mid Wheels (Per Track)	4
Other	
PTO	1 ¾" - 1000 rpm
Safety Chains (Grade 70)	(2) 40.5K lbs. Rated
Adjustable Discharge Spout	28 Degrees
Hydraulic Requirements	2 SCVs

1500

Capacity: 1500 bushels¹
Heaped Capacity: 1600 bushels¹
Unloads: 750 bu/min²



DIMENSIONS

Weight	
Flotation (Empty)	N/A
Row Crop (Empty)	N/A
Track (Empty)	35,180 lbs.
Hitch (Empty)	5,250 lbs.
Hitch (Loaded) ¹	7,380 lbs.
Width – Overall	
Flotation	N/A
Row Crop 30"	N/A
Row Crop, Wide Row	N/A
Track	13'
Height - Overall	
	11' 4"
Length - Total:	
	38' 10"

SPECIFICATIONS

Vertical Auger	24" Diameter
Horizontal Auger	22" Diameter
Drive Belts	4-Band V Belts (2)
Flotation Tire	
Hubs (Cast Ductile Iron)	N/A
Spindle	N/A
Row Crop	
Hubs (Cast Ductile Iron)	N/A
Spindle	N/A
Track	
Track Width	36"
Ground Contact Length	108"
Total Footprint (sq. in.)	7,776
End Wheels (Per Track)	(2) 36 ½"
Mid Wheels (Per Track)	4
Other	
PTO	1 ¾" - 1000 rpm
Safety Chains (Grade 70)	(2) 40.5K lbs. Rated
Adjustable Discharge Spout	28 Degrees
Hydraulic Requirements	2 SCVs

¹ Cart capacity and hitch weight are based on #2 corn at 15% moisture (56lb test weight). Cart capacity and hitch weight may vary based on crop type, grade, moisture and other environmental factors. ² Bushels per minute may vary with moisture content of grain and/or PTO rpm.