

MODELS/SPECS

851

Capacity: 30 m³ | Unloads: 17 m³/min



DIMENSIONS & SPECIFICATIONS

Weight	
Radial Tires (Empty)	6,640 kg
Tracks by Camso (Empty)	N/A
Hitch (Empty)	1,135 kg
Hitch (Loaded) ¹	2,270 kg
Width - Overall	
Radial Tires	4.1 m
Height	
Short Side Height	3.4 m
High Side Height	3.7 m
Length - Overall	
Length	8.6 m
UltraFlyte™ Auger	
Diameter	51 cm
Reach	2.2 m
Height	4.1 m
Other	
Hydraulic Requirements	3 SCVs
PTO	1 ¾" - 1,000 rpm

1051

Capacity: 37 m³ | Unloads: 17 m³/min



DIMENSIONS & SPECIFICATIONS

Weight	
Radial Tires (Empty)	6,850 kg
Tracks by Camso (Empty)	10,400 kg
Hitch (Empty)	1,135 kg
Hitch (Loaded) ¹	2,270 kg
Width - Overall	
Radial Tires & Tracks	4.1 m
Height	
Short Side Height	3.5 m
High Side Height	3.8 m
Length - Overall	
Length	9.25 m
UltraFlyte™ Auger	
Diameter	51 cm
Reach	2.2 m
Height	4.1 m
Other	
Hydraulic Requirements	3 SCVs
PTO	1 ¾" - 1,000 rpm

¹ Cart capacity and hitch weight are based on #2 corn at 15% moisture (56 lb. test weight). Cart capacity and hitch weight may vary based on crop type, grade, moisture and other environmental factors. ² Unload rates may vary with moisture content of grain and/or PTO rpm.