

TIRE & TRACK OPTIONS

Kinze Single Auger Grain Carts come with either diamond or lug tread radial tires, or high performance Kinze tracks by Camso, matched to your farming operation.



Low Ground Pressure Radial Diamond Tires

Diamond tread radial tires provide very low ground contact pressure to minimize soil compaction. Standard 20-bolt hubs ensure the heaviest loads remain balanced.

IF900/65R32CF0/191B(R3)

Low Ground Pressure Radial Lug Tires

For great mud handling performance in a radial tire, a lug version is available. Standard 20-bolt hubs ensure the heaviest loads remain balanced.

IF900/60R32CF0/188B(R1)



NEW Kinze Tracks by Camso (1051 Only)

Rough fields and wet conditions create no delays with a grain cart equipped with tracks. High performance, 36" wide, Kinze tracks by Camso have 100" of ground contact. Oscillating bogie wheels allow for less berming and smoother operation with reduced rolling resistance. Less maintenance and increased up-time is achieved with oil bath hubs and spring track tensioner. See Kinze.com for more information.

MODELS/SPECS

851

Capacity: 850 bushels¹ | Unloads: 475 bu/min²



DIMENSIONS & SPECIFICATIONS

Weight	
Radial Tires (Empty)	14,640 lbs.
Tracks by Camso (Empty)	N/A
Hitch (Empty)	2,500 lbs.
Hitch (Loaded) ¹	5,000 lbs.
Width - Overall	
Radial Tires	13' 5"
Height	
Short Side Height	11' 1"
High Side Height	12' 1"
Length - Overall	
Length	28' 4"
UltraFlyte™ Auger	
Diameter	20"
Reach	7' 3"
Height	13' 4"
Other	
Hydraulic Requirements	3 SCVs
PTO	1 3/4" - 1000 rpm

1051

Capacity: 1050 bushels¹ | Unloads: 475 bu/min²



DIMENSIONS & SPECIFICATIONS

Weight	
Radial Tires (Empty)	15,100 lbs.
Tracks by Camso (Empty)	23,000 lbs.
Hitch (Empty)	2,500 lbs.
Hitch (Loaded) ¹	5,000 lbs.
Width - Overall	
Radial Tires & Tracks	13' 5"
Height	
Short Side Height	11' 7"
High Side Height	12' 7"
Length - Overall	
Length	30' 4"
UltraFlyte™ Auger	
Diameter	20"
Reach	7' 3"
Height	13' 4"
Other	
Hydraulic Requirements	3 SCVs
PTO	1 3/4" - 1000 rpm

¹ Cart capacity and hitch weight are based on #2 corn at 15% moisture (56 lb. test weight). Cart capacity and hitch weight may vary based on crop type, grade, moisture and other environmental factors. ² Bushels per minute may vary with moisture content of grain and/or PTO rpm.