MANUFACTURER'S NAME EARTH WORKS Natural Organics Products ADDRESS (NUMBER, STREET, CITY, STATE, ZIP) 1500 UHLER ROAD, EASTON, PA 18040 CHEMICAL NAME AND SYNONYMS LIQUID PLANT NUTRIENT PROPRIETARY FORMULATION OF PLA & BIOLOGICAL MATERIALS SECTION III - HAZARDOUS INGREDIENTS PAINTS, PRESERVATIVES & TLV SOLVENTS PAINTS, PRESERVATIVES & (UNITS) PROPRIETARY FORMULATION OF PLA & BIOLOGICAL MATERIALS PAINTS, PRESERVATIVES & (UNITS) PROPRIETARY FORMULATION OF PLA & BIOLOGICAL MATERIALS PAINTS, PRESERVATIVES & (UNITS) PROPRIETARY FORMULATION OF PLA & BIOLOGICAL MATERIALS PALLOYS AND METAL OCATINGS PAINTS, PRESERVATIVES & (UNITS) PROPRIETARY FORMULATION OF PLA & BIOLOGICAL MATERIALS PAINTS, PRESERVATIVES & (UNITS) PROPRIETARY FORMULATION OF PLA & BIOLOGICAL MATERIALS PAINTS, PRESERVATIVES & (UNITS) PROPRIETARY FORMULATION OF PLA & BIOLOGICAL MATERIALS PAINTS, PRESERVATIVES OF OTHER LIQUID OF THE PROPRIETARY FORMULATION OF PLA ADDITIVES O OTHERS O OT	otein Plus		
EARTH WORKS Natural Organics Products ADDRESS (NUMBER, STREET, CITY, STATE, ZIP) 1500 UHLER ROAD, EASTON, PA 18040 CHEMICAL NAME AND SYNONYMS LIQUID PLANT NUTRIENT CHEMICAL FAMILY BOTANICAL OCEAN VARITETY SECTION II- HAZARDOUS INGREDIENTS PAINTS, PRESERVATIVES & TLV ALLOYS AND METAL COATINGS 9,6 PIGMENTS 0 BASE METAL 0 0 CATALYST 0 METTALLIC COATINGS 0 SOLVENTS 0 OTHERS 0 OTHER LIQUIDS, SOLIDS, OR GASES 9,6 HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES 9,6 BOILING POINT (° F) N/A SPECIFIC GRAVITY (HPO = 1) VAPOR PRESSURE (mm Hg.) N/A PERCENT, VOLATILE BY VOLUME (%) VAPOR DENSITY (AIR = 1) N/A EVAPORATION RATE (_ = 1) SOLUBILITY IN WATER 100% APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A			
EARTH WORKS Natural Organics Products ADDRESS (NUMBER, STREET, CITY, STATE, ZIP) 1500 UHLER ROAD, EASTON, PA 18040 CHEMICAL NAME AND SYNONYMS LIQUID PLANT NUTRIENT CHEMICAL PAMILY BOTANICAL OCEAN VARITETY PAINTS, PRESERVATIVES & TILV SOLVENTS PIGMENTS O BASE METAL O CATALYST O HALLOYS VEHICLE O METTALLIC COATINGS OTHERS O HELER METAL PLUS COATING OR CORE FILUX ADDITIVES O THERS O THERS O THERS O HELER METAL PLUS COATING OR CORE FILUX ADDITIVES O THERS O THE	11		
EMERGENCY TEL. No.610-250-9.	11		
1500 UHLER ROAD, EASTON, PA 18040 CHEMICAL NAME AND SYNONYMS	25.00		
TRADE NAME AND SYNONYMS LIQUID PLANT NUTRIENT CHEMICAL FAMILY BOTANICAL OCEAN VARITETY PROPRIETARY FORMULATION OF PLA & BIOLOGICAL MATERIALS SECTION II-HAZARDO US INGREDIENTS PAINTS, PRESERVATIVES & TLV ALLOYS AND METAL COATINGS SOLVENTS PIGMENTS O BASE METAL O CATALYST O ALLOYS SOLVENTS O FILLER METAL PLUS COATING OR CORE FLUX ADDITIVES O THERS O THERS O THERS O THAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES NONE SECTION III-PHYSICAL DATA BOILING POINT (° F) N/A SPECIFIC GRAVITY (HPO = 1) VAPOR PRESSURE (mm Hg.) N/A PERCENT, VOLATILE BY VOLUME (%) VAPOR DENSITY (AIR = 1) SOLUBILITY IN WATER APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV-FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC EXTING MEDIA	EMERGENCY TEL. NO.610-250-9560		
CHEMICAL FAMILY BOTANICAL OCEAN VARITETY BOTANICAL OCEAN VARITETY SECTION II-HAZARDOUS INGREDIENTS PAINTS, PRESERVATIVES & TLV ALLOYS AND METAL COATINGS PIGMENTS CATALYST O CATALYST O CHICLE O SOLVENTS O TILLE METALLIC COATINGS O VEHICLE O THERS TH			
CHEMICAL FAMILY BOTANICAL OCEAN VARITETY BOTANICAL OCEAN VARITETY SECTION II-HAZARDOUS INGREDIENTS PAINTS, PRESERVATIVES & TLV ALLOYS AND METAL COATINGS PIGMENTS CATALYST O CATALYST O CHICLE O SOLVENTS O TILLE METALLIC COATINGS O VEHICLE O THERS TH			
BOTANICAL OCEAN VARITETY SECTION II- HAZARDO US INGREDIENTS PAINTS, PRESERVATIVES & TLV COATINGS % PIGMENTS 0 BASE METAL 0 CATALYST 0 ALLOYS NO METALLIC COATINGS 0 VEHICLE 0 METALLIC COATINGS 0 SOLVENTS 0 FILLER METAL PLUS COATING OR CORE FLUX ADDITIVES 0 OTHERS 0 OTHERS 0 OTHERS 0 HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES % PONE SECTION III- PHYSICAL DATA BOILING POINT (° F) N/A SPECIFIC GRAVITY (H°O = 1) VAPOR PRESSURE (mm Hg.) N/A EVAPORATION RATE (_ = 1) SOLUBILITY IN WATER 100% APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA	FORMULA		
PAINTS, PRESERVATIVES & TLV SOLVENTS PAINTS, PRESERVATIVES & TLV (UNITS) PIGMENTS O CATALYST O VEHICLE O SOLVENTS O SOLVENTS O SOLVENTS O ALLOYS O METTALLIC COATINGS O FILLER METAL PLUS COATINGS O FILLER METAL PLUS COATING OR CORE FLUX ADDITIVES O OTHERS O THAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES NONE SECTION III- PHYSICAL DATA BOILING POINT (° F) VAPOR PRESSURE (mm Hg.) VAPOR DENSITY (AIR = 1) SOLUBILITY IN WATER 100% APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC EXTINGUISHING MEDIA	ANT NUTRIENTS		
SOLVENTS			
PIGMENTS	TLV (UNITS)		
CATALYST 0 ALLOYS 0 VEHICLE 0 METTALLIC COATINGS 0 SOLVENTS 0 FILLER METAL PLUS COATING OR CORE FILUX 0 ADDITIVES 0 OTHERS 0 OTHERS 0 OTHERS 0 HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES % NONE NONE SECTION III- PHYSICAL DATA BOILING POINT (° F) N/A SPECIFIC GRAVITY (H²O = 1) VAPOR PRESSURE (mm Hg.) N/A PERCENT, VOLATILE BY VOLUME (%) VAPOR DENSITY (AIR = 1) N/A EVAPORATION RATE (_ = 1) SOLUBILITY IN WATER 100% APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA N/A	(CIVII)		
VEHICLE 0			
ADDITIVES 0 OTHERS 0 HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES **NONE **SECTION III- PHYSICAL DATA** BOILING POINT (° F) VAPOR PRESSURE (mm Hg.) VAPOR DENSITY (AIR = 1) SOLUBILITY IN WATER APPEARANCE AND ODOR: GREEN/BROWN LIQUID **SECTION IV- FIRE AND EXPLOSION HAZARD DATA** FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A **EXTINGUISHING MEDIA**			
ADDITIVES 0 OTHERS 0 OTHERS 0 HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES % NONE SECTION III- PHYSICAL DATA BOILING POINT (° F) N/A SPECIFIC GRAVITY (H²O = 1) VAPOR PRESSURE (mm Hg.) N/A PERCENT, VOLATILE BY VOLUME (%) VAPOR DENSITY (AIR = 1) N/A EVAPORATION RATE (_ = 1) SOLUBILITY IN WATER 100% APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A			
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES NONE SECTION III- PHYSICAL DATA BOILING POINT (° F) N/A VAPOR PRESSURE (mm Hg.) N/A PERCENT, VOLATILE BY VOLUME (%) VAPOR DENSITY (AIR = 1) N/A EVAPORATION RATE (_ = 1) SOLUBILITY IN WATER 100% APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA			
SECTION III- PHYSICAL DATA BOILING POINT (° F) VAPOR PRESSURE (mm Hg.) VAPOR DENSITY (AIR = 1) SOLUBILITY IN WATER APPEARANCE AND ODOR: GREEN/BROWN LIQUID FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA			
SECTION III- PHYSICAL DATA BOILING POINT (° F) VAPOR PRESSURE (mm Hg.) VAPOR DENSITY (AIR = 1) SOLUBILITY IN WATER APPEARANCE AND ODOR: GREEN/BROWN LIQUID FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA	TLV (UNITS)		
BOILING POINT (° F) N/A SPECIFIC GRAVITY (H²O = 1) VAPOR PRESSURE (mm Hg.) N/A PERCENT, VOLATILE BY VOLUME (%) VAPOR DENSITY (AIR = 1) N/A EVAPORATION RATE (_ = 1) SOLUBILITY IN WATER 100% APPEARANCE AND ODOR: GREEN/BROWN LIQUID FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA	(01.112)		
VAPOR PRESSURE (mm Hg.) N/A PERCENT, VOLATILE BY VOLUME (%) VAPOR DENSITY (AIR = 1) N/A EVAPORATION RATE (_ = 1) SOLUBILITY IN WATER 100% APPEARANCE AND ODOR: GREEN/BROWN LIQUID FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA			
VAPOR DENSITY (AIR = 1) SOLUBILITY IN WATER APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A	1.2		
SOLUBILITY IN WATER 100% APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA	N/A		
APPEARANCE AND ODOR: GREEN/BROWN LIQUID SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA	N/A		
SECTION IV- FIRE AND EXPLOSION HAZARD DATA FALSH POINT (METHOD USED) FLAMMABLE LIMITS 545 °F COC N/A EXTINGUISHING MEDIA			
FALSH POINT (METHOD USED) 545 °F COC EXTINGUISHING MEDIA			
545 °F COC N/A EXTINGUISHING MEDIA			
EXTINGUISHING MEDIA	LEL UEL		
DRY CHEMICAL CARROLL RIOWER WATER TO AM			
DRY CHEMICAL, CARBON DIOXIDE, WATER, FOAM			
SPECIAL FIRE FIGHTING PROCEDURES			
AVOID BREATHING FUMES FROM FIRE UNUSUAL FIRE AND EXPLOSION HAZARDS			
USE SELF-CONTAINED AIR SUPPLY			

SECTION V- HEALTH HAZARD DATE			
THRESHOLD LIMIT VALUE			
N/A			
EFFECTS OF OVEREXPOSURE			
MAY CAUSE EYE DAMAGE		AUSEA IF INGESTED	
EMERGENCY AND FIRST AID PROCE	DUKES		
FLUSH WITH WATER	CECTION VI DE		
STABILITY	UNSTABLE:	CACTIVITY DATA CONDITIONS TO AVOID:	
STABILITI	UNSTABLE.		
	STABLE: X	EXTREME HEAT OR FREEZING MAY CAUSE PRODUCT TO SEPERATE	
INCOMPATIBILITY (MATERIALS TO A	AVOID)		
NONE			
HAZARDOUS DECOMPOSITION PROD	DUCTS		
NONE			
HAZARDOUS POLYMERIZATION		MAY OCCUR:	
		WILL NOT OCCUR: X	
SECTION VII- SPILL OR LEAK PROCEDURES			
STEPS TO BE TAKEN IN CASE MATER		R LEAR I ROCEDURES	
CONTAIN SPILL BY DIKING	G WITH SOIL OR SAND		
WASTE DISPOSAL METHOD	WIII BOIL OR BAND		
DISPOSE OF IN ACCORDAN	ICE WITH FEDERAL, STATE	E AND LOCAL REGULATIONS.	
SECTION VIII- SPECIAL PROTECTION INFORMATION			
RESPIRATORY PROTECTION (SPECIFY TYPE)			
AIR PURIFYING RESPIRATO		CESSARY	
VENTILATION	LOCAL EXHAUST	SPECIAL	
NORMAL	MECHANICAL (GENERAL)	OTHER	
		EYE PROTECTION	
PROTECTIVE GLOVES			
PROTECTIVE GLOVES RUBBER		SAFETY GOGGLES	
RUBBER			
RUBBER OTHER PROTECTIVE EQUIPMENT			
RUBBER	SECTION IX. SPEC	SAFETY GOGGLES	
RUBBER OTHER PROTECTIVE EQUIPMENT			
RUBBER OTHER PROTECTIVE EQUIPMENT NONE	IDLING AND STORING	SAFETY GOGGLES	
RUBBER OTHER PROTECTIVE EQUIPMENT NONE PRECAUTIONS TO BE TAKEN IN HAN	IDLING AND STORING	SAFETY GOGGLES	