



**FLOATING SYSTEM** 000 REZILLLOCK

OATIN

## SYSTEM FEATURES AND BENEFITS

A floating sports floor system providing uniform play consisting in general of a vapor barrier, blanket foam underlayment, two layers nominal 1" x 6" softwood subfloor, maple flooring, sanding, sealers, finishes, game lines and wall base.



- (1) Foam Blanket
- 2) Nominal 1" x 6" (19 mm x 140 mm) softwood subfloor

WALL BASE DETAIL (RezillPanel)

ISO9001:2008

SYSTEM TYPE

Floating

ANCHORAGE

No concrete attachment

SUBFLOOR CONSTRUCTION

Softwood Sleepers

RESILIENCE

Closed Cell Blanket Foam

SLAB DEPRESSION

25/32" (20 mm) flooring - 2 1/2" (64 mm) 33/32" (26 mm) flooring - 2 3/4" (70 mm)

Adjust slab depression accordingly when replacing 1/4" (6 mm) foam with other thickness

TESTING LABORATORY

United States Sports Surfacing Laboratory

USSL

CERTIFIED TESTING

Laboratory test equipment calibrated and certified through the ISSS

**GREEN STATUS** 



Managed forests, certification available

x 4" (76 mm x 102 mm) Vent Base 1 1/2" (38 mm) Expansion Space Nominal 1" x 6" (19 mm x 140 mm) Softwood Subfloor 25/32" x 2 1/4"(20 mm x 57 mm) Laytite Maple Closed Cell Blanket Foam 1/2" (64 mm) Concrete Slab THRESHOLD DETAIL (optional accessory)

Aluminum Threshold

1 1/2" (38 mm) Expansion Space Closed Cell Blanket Nominal 1" x 6" (19 mm x 140 mm) Softwood Subflo<mark>or</mark> Vapor Barrier °Concrete Slab

EQUIPMENT DETAIL (optional accessory)

Equipment S**l**eeve Closed Cell Blanket Foam Floor Plate 25/32" x 2 1/4" (20 mm x 57 mm)

connorfloor.com 1.800.283.9522

 $\bigcirc$