

Application

Upholstered Walls, Walls

Characteristics

Content: 53% Polyester, 47% Polyethylene

Finish: Stain Repellent Backing: Acrylic

Width: 54" (137cm)

Bolt Size: 57 yards (52 m) Weight: 11 oz/ly (300 gr/lm)

Traffic: High Traffic

Country of Origin: Canada

Note: Variations in color and texture are inherent to

this textile.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$43.00 / C\$61.75 (FOB destination) C\$58.25 (FOB origin)

Testing

Acoustics: ASTM C423, 0.85 NRC

Flammability: AS/NZS 3837 Adhered

AS/NZS 3837 Unadhered

ASTM E 84 Adhered ASTM E 84 Unadhered BS 476 Unadhered* EN 13501 Adhered*

EN 13501 Unadhered* ISO 5660 Adhered ISO 5660 Unadhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Environmental

Greenguard Gold Certified FR Free

Warranty

10 years: Walls

3 years: Upholstered Walls.

See Terms and Conditions for more information.

© 2019 Maharam

Last updated April 1, 2024