

300025 Spun maharam

Application

Walls

Characteristics

Content: 70% Cellulose, 30% Polyester Finish: PFAS-Free Water Repellent Backing: Cellulose / Polyester

Width: 54" (137cm)

Bolt Size: 110 yards (101 m) Weight: 7.1 oz/ly (200 gr/lm) Traffic: Moderate Traffic

Country of Origin: Netherlands

Note: Variations in color and texture are inherent to

this textile.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$38.00 /

Testing

Flammability: ASTM E 84 Adhered

EN 13501 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Maintenance

X-Vacuum or brush lightly to remove surface dust.

₩ № 図 図 ※ 図 ※

Environmental

Greenguard Gold Certified Healthier Hospitals Compliant

LBC Red List Free REACH Compliant

Contains Bio-Based Content

Contains Forest Stewardship Council (Fsc) Certified

Content FR Free

Free of Intentionally Added PFAS

Warranty

1 year. See Terms and Conditions for more information.

© 2019 Maharam

Last updated April 1, 2024