

300040 Filigree

maharam

Application Walls

maharam.com.

Characteristics Content: 100% Non-Phthalate Vinyl Finish: None Backing: Polyester/Cotton Osnaburg Width: 54" (137cm) Repeat: Non-match Bolt Size: 30 yards (27 m) Class: Type II Weight: 20 oz/ly (600 gr/lm) Traffic: High Traffic Country of Origin: USA Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation

Guidelines included in each shipment or available at

Price \$38.50 / C\$55.75 (FOB destination) C\$52.25 (FOB origin)

Testing Flammability: AS/NZS 3837 Adhered ASTM E 84 Adhered BS 476 Adhered* CAN ULC S102 Adhered EN 13501 Adhered* GB 8624 Adhered* *passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours

MaintenanceW/B-Clean with water-based cleanser or dilutedhousehold bleach. $\boxtimes \bigtriangleup \boxtimes \boxtimes$

Environmental Greenguard Certified FR Free Free of Intentionally Added PFAS Non-Phthalate Vinyl

Warranty

10 years. See Terms and Conditions for more information.

© 2019 Maharam

Last updated April 1, 2024

maharam