

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled

Polyester

Width: 52" (132cm) Repeat: 24 1/4" V, 52" H (62cm V, 132cm H)

Bolt Size: 30 yards (27 m) Weight: 8.5 oz/ly (300 gr/lm)

Traffic: Moderate Traffic Country of Origin: USA

Note: This product is available in custom colors for a

minimum of 30 yards.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$61.00 / C\$86.00 (FOB destination) C\$82.50 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E 84 Adhered CAN ULC S102 Adhered EN 13501 Adhered* ISO 5660 Adhered *passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Maintenance

W-Clean with water-based cleanser.



Environmental

Greenguard Gold Certified Healthier Hospitals Compliant LBC Red List Free Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Warranty

3 years. See Terms and Conditions for more information.

© 2019 Maharam

Last updated April 1, 2024