

Application

Upholstered Walls, Walls

Characteristics

Content: 55% Polyester, 45% Solution-Dyed

Polyolefin

Finish: Stain Repellent

Backing: Acrylic Width: 56" (142cm)

Bolt Size: 40 yards (37 m) Weight: 15.3 oz/ly (500 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation

Guidelines included in each shipment or available at

maharam.com.

Price

\$32.00 / C\$46.75 (FOB destination)

C\$43.25 (FOB origin)

Testing

Acoustics: ASTM C423, 0.80 NRC

Flammability: ASTM E 84 Adhered

ASTM E 84 Unadhered CAN ULC S102 Adhered CAN ULC S102 Unadhered EN 13501 Adhered*

EN 13501 Adhered* EN 13501 Unadhered* GB 8624 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Maintenance

W/S/B-Clean with water-based cleanser; mild, waterfree dry cleaning solvent, or diluted household

bleach.

Environmental

Greenguard Gold Certified

REACH Compliant

FR Free

Warranty

10 years: Walls

3 years: Upholstered Walls.

See Terms and Conditions for more information.

© 2022 Maharam

Last updated April 1, 2024