

Application

Walls

Characteristics

Content: 41% Post-Consumer Recycled Polyester, 40%

Non-Phthalate Vinyl, 19% Polyester Finish: PFAS-Free Water Repellent

Backing: Acrylic Width: 54" (137cm) Bolt Size: 28 yards (26 m) Weight: 17.2 oz/ly (500 gr/lm)

Country of Origin: Canada

Traffic: High Traffic

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$40.00 / C\$57.75 (FOB destination) C\$54.25 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered ASTM E 84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 200+ hours



Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

 $\boxtimes \triangle \boxtimes \boxtimes \otimes$

Environmental

Greenguard Gold Certified Contains Recycled Content FR Free Free of Intentionally Added PFAS

Warranty

10 years. See Terms and Conditions for more information.

© 2021 Maharam

Last updated April 1, 2024