

399426 Sari maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester/Cotton Osnaburg

Width: 54" (137cm) Repeat: Non-match Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (600 gr/lm)

Traffic: High Traffic Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$32.50 / C\$47.50 (FOB destination) C\$44.00 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E 84 Adhered BS 476 Adhered*

CAN ULC S102 Adhered

EN 13501 Adhered GB 8624 Adhered* ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Environmental

FR Free

Free of Intentionally Added PFAS

Non-Phthalate Vinyl

Warranty

10 years. See Terms and Conditions for more information.

© 2009 Maharam

Last updated April 1, 2024