



Design

Vik Muniz

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 9' 8" W (305cm x 295cm)

Traffic: Moderate Traffic Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis.

Maintenance

W-Clean with water-based cleanser.

図☆図☆◎

Testing

Flammability: AS/NZS 3837 Adhered ASTM E 84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free

k rree

Free of Intentionally Added PFAS

Brief

Related to the 2008 series Pictures of Garbage, Vik Muniz's Fleur De Lys delves into the divide that separates both art and design and the decorative and the functional.

Warranty

3 years. See Terms and Conditions for more information.

© 2010 Vik Muniz, Maharam under license

Last updated April 1, 2024