



Design

Jacob Hashimoto

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' H x 20' W (305cm x 610cm)

Traffic: Moderate Traffic Customs: Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis.

Maintenance

W-Clean with water-based cleanser.

図☆図☆◎

Testing

Flammability: AS/NZS 3837 Adhered ASTM E 84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Brief

Using black monofilament, Jacob Hashimoto arranges kites in a floating tapestry, forming a complex matrix that is at once dense and ethereal. Silent Rhythm is a seamless digital assemblage of sixty-four photographs documenting an installation by Hashimoto for Maharam Digital Projects.

Warranty

3 years. See Terms and Conditions for more information.

© 2011 Jacob Hashimoto, Maharam under license

Last updated April 1, 2024