



003 Doe



004 Beige



005 Mill



006 Cloud



007 Shool



008 Dorado



013 Porpoise



014 Atmosphere



016 Arctic



017 Placid

399634 Cue

maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl
Finish: None
Backing: Polyester/Cotton Osnaburg
Width: 54" (137cm)
Repeat: Non-match
Bolt Size: 30 yards (27 m)
Class: Type II
Weight: 20 oz/ly (600 gr/lm)
Traffic: High Traffic
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price


\$27.50 / C\$40.75 (FOB destination)
C\$37.25 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered
ASTM E 84 Adhered
BS 476 Adhered*
CAN ULC S102 Adhered
EN 13501 Adhered*
GB 8624 Adhered*
ISO 5660 Adhered
*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours


Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.


Environmental

FR Free
Free of Intentionally Added PFAS
Non-Phthalate Vinyl

Warranty

10 years. See Terms and Conditions for more information.

© 2014 Maharam

Last updated April 1, 2024