


001 Malha



002 Pave



003 Foiled



004 Flounder



005 Karst



006 Gelid



007 Hemlock



008 Gallant



009 Kernel




010 Yam



011 Squid




013 Violin




015 Valor



016 Dewdrop



017 Fluvial



018 Kelp



019 Hunter



Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl  
Finish: None  
Backing: Polyester/Cotton Osnaburg  
Width: 54" (137cm)  
Bolt Size: 30 yards (27 m)  
Class: Type II  
Weight: 20 oz/ly (600 gr/lm)  
Traffic: High Traffic  
Country of Origin: USA  
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.  
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$22.00 / C\$33.25 (FOB destination)  
C\$29.75 (FOB origin)

Testing

Flammability: AS/NZS 3837 Adhered  
ASTM E 84 Adhered  
BS 476 Adhered\*  
CAN ULC S102 Adhered  
EN 13501 Adhered\*  
GB 8624 Adhered\*  
\*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.



Environmental

FR Free  
Free of Intentionally Added PFAS  
Non-Phthalate Vinyl

Warranty

10 years. See Terms and Conditions for more information.

© 2018 Maharam

Last updated April 1, 2024