



Flamingo™ auto scrub pad

PRODUCT SPECIFICATIONS

1.0 Description

The Flamingo Auto Scrub Pad is constructed of polyester fibers in an open texture nonwoven fabrication and is designed for cleaning. Abrasive particles are dispersed throughout and bonded to the nonwoven construction with a durable adhesive.

2.0 Properties

Property	Value
Thickness	1 in 26 mm
Weight	28 osy 949 gsm
Fiber Type	Recycled Polyester
Binder System	Cross-linkable water based
Binder Application	Spray/Dip
Abrasive Application	Spray/Dip
Abrasive	Yes
Color	Pink
Pack	5 per case*

*27" also available in 2 per case

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact Americo with any questions or concerns.

Maintex, Inc.
1-800-446-1888
www.maintex.com

Rev. 06/03/2019

3.0 Use

Use with neutral floor cleaning solutions to remove soil and black heel marks. This pad is also used to clean soiled hard surface floors such as concrete when used with appropriate cleaning chemicals. Ideal for use on machines speeds up to 350 rpm.

4.0 Construction

The Flamingo Auto Scrub Pad is constructed of polyester fibers and synthetic adhesives that will not be notably affected by water, detergents and cleaners normally used for floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides.

5.0 Labeling

Labeling is to clearly identify product, size, and quantity. Americo brand or private label is available for this product.

6.0 Environmental Initiatives

- Polyester fiber used in our pads come from 100% post consumer and industrial recycled waste product.
- Full Cycle™**, formulated to biodegrade* in a fraction of the time that it takes conventional floor pads once discarded into an active landfill.
- Water Based Latex Resins are used in the manufacturing process. No phenol-formaldehyde resins are used in our binding process.
- Shipping cartons contain at least 45% recycled material.
- Plant is operating under EPA approved Clean Air Permit.
- In-house water treatment has reduced our waste water flow by 83%.

* For complete details or to view ASTM D5511 test results visit www.AmericoFullCycle.com

7.0 Directions for Use

Use pad until soil and heel marks are removed from floor. Pick up cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic. Follow use with an Americo polishing pad to achieve high gloss.

8.0 Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil.

9.0 Sizes

Disc Size (Diameter) (O.D. ± 0.06 inch)	Center Hole
11 inch	3.25 inch
12 inch	3.25 inch
13 inch	3.25 inch
14 inch	3.25 inch
15 inch	3.25 inch
16 inch	3.25 inch
17 inch	3.25 inch
18 inch	3.25 inch
19 inch	3.25 inch
20 inch	3.25 inch
21 inch	3.25 inch
22 inch	3.25 inch
23 inch	3.25 inch
24 inch	3.25 inch
27 inch	3.25 inch

Additional sizes available.

Check for availability on additional center hole dimensions.